





THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
J	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
		A		REDRAWN W/CHANGE	ECR-12-021403	13DEC2012	TS KB



△ MUST BE KEPT BETWEEN -Z- AND 2mm
 2. APPLIED CAP HOUSING; 174467
 3. APPLIED CONTACT PART NUMBER; 173630 AND 173631

△ -Z- 面より 2mm の範囲で測定
 2. 嵌合相手ハウジング型番; 174467
 3. 内装するリセプタクルコンタクト型番 173630 及び 173631

自然色 (NATURAL)	174464-1
色 (COLOR)	型番 (PART NUMBER)

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T.SHINOHARA 13DEC2012	STE TE Connectivity													
DIMENSIONS: 単位: 耗 mm		CHK K.BETSUI 13DEC2012														
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差		APVD K.BUTSUI 13DEC2012	NAME 名称													
<table border="1"> <tr><td>0 PLC</td><td>± -</td></tr> <tr><td>1 PLC</td><td>± -</td></tr> <tr><td>2 PLC</td><td>± -</td></tr> <tr><td>3 PLC</td><td>± -</td></tr> <tr><td>4 PLC</td><td>± -</td></tr> <tr><td>ANGLES</td><td>± -</td></tr> </table>		0 PLC	± -	1 PLC	± -	2 PLC	± -	3 PLC	± -	4 PLC	± -	ANGLES	± -	PRODUCT SPEC 製品規格 108-5216	070 SERIES MULTI-LOCK CONNECTOR 10POSITION PLUG HOUSING	
0 PLC	± -															
1 PLC	± -															
2 PLC	± -															
3 PLC	± -															
4 PLC	± -															
ANGLES	± -															
MATERIAL 材料 PBT		FINISH 仕上 -	APPLICATION SPEC 取付適用規格 -	RESTRICTED TO 番号												
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差		WEIGHT -	SIZE A3	CAGE CODE 00779												
<table border="1"> <tr><td>10_±</td><td>: ±0.2</td></tr> <tr><td>30_±</td><td>> 10 : ±0.25</td></tr> <tr><td>100_±</td><td>> 30 : ±0.3</td></tr> <tr><td>ANGLE</td><td>: ±3°</td></tr> </table>		10 _±	: ±0.2	30 _±	> 10 : ±0.25	100 _±	> 30 : ±0.3	ANGLE	: ±3°	DRAWING NO 番号 C-174464		SCALE 尺度 2:1				
10 _±	: ±0.2															
30 _±	> 10 : ±0.25															
100 _±	> 30 : ±0.3															
ANGLE	: ±3°															
CUSTOMER DRAWING			SHEET 1 OF 1	REV A												

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)