

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	16MAR2017	RL	CW
	B	ECR-21-111798	18SEP2021	WQR	CW


NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
TUBE ID: 6.0mm
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING:  
PIN CONTACT: T209000210100X  
SOCKET CONTACT: T209000220100X  
SOCKET CONTACT,  
WITH SHUT OFF : T209001220100X)

注释:

- 技术参数:  
绝缘材料: PC  
导管内径: 6.0mm
- 气动端子需要单独订购。  
(订购号参考图面:  
公针: T209000210100X;  
母针: T209000220100X;  
带密闭气阀母针: T209001220100X)

T2111022301-000	HMN-PA2	HMN-PA2 MODULE INSERT HMN-PA2气动模块芯件
PART NUMBER 料号	PART DESCRIPTION 描述	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ROY LIU 16MAR2017	 TE Connectivity NAME HMN-PA2											
DIMENSIONS: mm		CHK KYLE ZENG 16MAR2017												
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD CHRIS WANG 16MAR2017												
<table border="1"> <tr> <td>0 PLC</td> <td>±-</td> </tr> <tr> <td>1 PLC</td> <td>±-</td> </tr> <tr> <td>2 PLC</td> <td>±-</td> </tr> <tr> <td>3 PLC</td> <td>±-</td> </tr> <tr> <td>4 PLC</td> <td>±-</td> </tr> <tr> <td>ANGLES</td> <td>±-</td> </tr> </table>		0 PLC			±-	1 PLC	±-	2 PLC	±-	3 PLC	±-	4 PLC	±-	ANGLES
0 PLC	±-													
1 PLC	±-													
2 PLC	±-													
3 PLC	±-													
4 PLC	±-													
ANGLES	±-													
MATERIAL	FINISH	APPLICATION SPEC -	SIZE A3	CAGE CODE -	DRAWING NO T2111022301000	RESTRICTED TO -								
-	-	WEIGHT -	CUSTOMER DRAWING		SCALE 3:2	SHEET 1 OF 1	REV B							

1470-19 (3/13)

Downloaded From [Onevac.com](http://Onevac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)