THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
AD	38

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	G	OG3C-0202-03	25APR03	TK	JO

1. TRUE POSITION TOLERANCE OF POST TIPS APPLIES WHEN HEADERS ARE HELD FLAT AGAINST POINTED CIRCUIT BOARD.

△2 OBSOLETE PART NUMBER

△3 .000100-.000200 BRIGHT TIN OVER .000050-.000100 NICKEL.

△4 .000100-.000200 BRIGHT TIN-LEAD OVER .000050-.000100 NICKEL.

△5 PRELIMINARY PART





RECOMMENDED HOLE LAYOUT

	△3	.125	.318	.500	5	.584	12	△5 4-87543-3
	△4	.125	.318	4.100	41	4.184	80	△2 4-87543-2
		.125	.318	4.000	40	4.084	80	△2 4-87543-1
		.125	.318	3.900	39	3.984	80	4-87543-0
		.125	.318	3.800	38	3.884	78	△2 3-87543-9
		.125	.318	3.700	37	3.784	76	△2 3-87543-8
		.125	.318	3.600	36	3.684	74	△2 3-87543-7
		.125	.318	3.500	35	3.584	72	△2 3-87543-6
SUPERCEDED BY 3-103322-5		.125	.318	3.400	34	3.484	70	3-87543-5
		.125	.318	3.300	33	3.384	68	△2 3-87543-4
		.125	.318	3.200	32	3.284	66	△2 3-87543-3
SUPERCEDED BY 3-103322-2		.125	.318	3.100	31	3.184	64	3-87543-2
		.125	.318	3.000	30	3.084	62	△2 3-87543-1
SUPERCEDED BY 3-103322-0		.125	.318	2.900	29	2.984	60	3-87543-0
SUPERCEDED BY 2-103322-5		.125	.318	2.800	28	2.884	58	△2 2-87543-9
		.125	.318	2.700	27	2.784	56	△2 2-87543-8
		.125	.318	2.600	26	2.684	54	△2 2-87543-7
		.125	.318	2.500	25	2.584	52	△2 2-87543-6
		.125	.318	2.400	24	2.484	50	2-87543-5
		.125	.318	2.300	23	2.384	48	△2 2-87543-4
		.125	.318	2.200	22	2.284	46	△2 2-87543-3
		.125	.318	2.100	21	2.184	44	△2 2-87543-2
SUPERCEDED BY 2-103322-1		.125	.318	2.000	20	2.084	42	2-87543-1
		.125	.318	1.900	19	1.984	40	2-87543-0
		.125	.318	1.800	18	1.884	38	△2 1-87543-9
		.125	.318	1.700	17	1.784	36	△2 1-87543-8
		.125	.318	1.600	16	1.684	34	1-87543-7
SUPERCEDED BY 1-103322-6		.125	.318	1.500	15	1.584	32	1-87543-6
		.125	.318	1.400	14	1.484	30	1-87543-5
		.125	.318	1.300	13	1.384	28	△2 1-87543-4
		.125	.318	1.200	12	1.284	26	1-87543-3
SUPERCEDED BY 1-103322-2		.125	.318	1.100	11	1.184	24	1-87543-2
		.125	.318	1.000	10	1.084	22	1-87543-1
		.125	.318	.900	9	.984	20	1-87543-0
SUPERCEDED BY 103322-9		.125	.318	.800	8	.884	18	87543-9
		.125	.318	.700	7	.784	16	87543-8
		.125	.318	.600	6	.684	14	87543-7
		.125	.318	.500	5	.584	12	87543-6
		.125	.318	.400	4	.484	10	87543-5
		.125	.318	.300	3	.384	8	87543-4
		.125	.318	.200	2	.284	6	87543-3
SUPERCEDED BY 103322-2		.125	.318	.100	1	.184	4	87543-2
	△4	.125	.318	-	-	.084	2	87543-1
	FINISH	E	D	C	B	A	NO OF POSN	PART NUMBER

87543

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -
ANGLES ± -

MATERIAL: HSC-GLASS FILLED NYLON COLOR: BLACK CONTACT-PHOS BRONZE

FINISH: SEE TABLE

DWN M.E.PASTEL 11-20-87
CHK T.C. CLARK 11-25-87
APVD T.C. CLARK 11-25-87
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

tyco Electronics — Tyco Electronics Corporation, Harrisburg, Pa

NAME: ASSEMBLY, MOD II, HEADER, DOUBLE ROW, .100X.100

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-87543	—

CUSTOMER DRAWING — SCALE 1:1 — SHEET 1 OF 1 — REV G

AMP 1471-9 REV 31MAR2000

H:\dmmod\

Downloaded From Oneyac.com

单击下面可查看定价，库存，交付和生命周期等信息

>>TE Connectivity(泰科)

Downloaded From Oneyac.com