



1 MATERIAL: CONNECTOR-NYLON UL94V-2 (GREEN).
 CONTACTS-0.30 [.012] THICK COPPER ALLOY
 0.00076 [.000030] GOLD IN OR 0.00076[.000030]
 TOTAL GOLD FLASH OVER PALLADIUM NICKEL,
 PER TE CONNECTIVITY'S DISCRETION, CONTACT AREA
 WITH BRIGHT TIN-LEAD FOR 641244-2 THRU
 1-641244-4, MATTE WHISKER MITIGATED TIN
 FOR 3-641244-2 THRU 4-641244-4 OVER
 NICKEL UNDERPLATE.

- 2 CONTACTS ACCEPT 28 AWG WIRE WITH 1.52 [.060] MAX INSULATION DIAMETER.
- 3 CONTACTS MUST ACCEPT 0.64±0.03 [.025±.001] SQUARE POST AND REMAIN LOCKED IN POSITION.
- 4 IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY NOT APPEAR ON ALL ASSEMBLIES.
- 5 DIMENSIONS IN BRACKETS ARE IN INCHES.
- 6 HOUSING FEATURES ARE: FEED THRU WITH LOCKING RAMP.
- 7 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

71.12 [2.800]	28	5-641244-8
68.58 [2.700]	27	5-641244-7
66.04 [2.600]	26	5-641244-6
63.50 [2.500]	25	5-641244-5
60.96 [2.400]	24	5-641244-4
58.42 [2.300]	23	5-641244-3
55.88 [2.200]	22	5-641244-2
53.34 [2.100]	21	5-641244-1
50.80 [2.000]	20	5-641244-0
48.26 [1.900]	19	4-641244-9
45.72 [1.800]	18	4-641244-8
43.18 [1.700]	17	4-641244-7
40.64 [1.600]	16	4-641244-6
38.10 [1.500]	15	4-641244-5
35.56 [1.400]	14	4-641244-4
33.02 [1.300]	13	4-641244-3
30.48 [1.200]	12	4-641244-2
27.94 [1.100]	11	4-641244-1
25.40 [1.000]	10	4-641244-0
22.86 [.900]	9	3-641244-9
20.32 [.800]	8	3-641244-8
17.78 [.700]	7	3-641244-7
15.24 [.600]	6	3-641244-6
12.70 [.500]	5	3-641244-5
10.16 [.400]	4	3-641244-4
7.62 [.300]	3	3-641244-3
5.08 [.200]	2	3-641244-2
DIM A	NO.OF POSN	ASSEMBLY

71.12 [2.800]	28	2-641244-8
68.58 [2.700]	27	2-641244-7
66.04 [2.600]	26	2-641244-6
63.50 [2.500]	25	2-641244-5
60.96 [2.400]	24	2-641244-4
58.42 [2.300]	23	2-641244-3
55.88 [2.200]	22	2-641244-2
53.34 [2.100]	21	2-641244-1
50.80 [2.000]	20	2-641244-0
48.26 [1.900]	19	1-641244-9
45.72 [1.800]	18	1-641244-8
43.18 [1.700]	17	1-641244-7
40.64 [1.600]	16	1-641244-6
38.10 [1.500]	15	1-641244-5
35.56 [1.400]	14	1-641244-4
33.02 [1.300]	13	1-641244-3
30.48 [1.200]	12	1-641244-2
27.94 [1.100]	11	1-641244-1
25.40 [1.000]	10	1-641244-0
22.86 [.900]	9	641244-9
20.32 [.800]	8	641244-8
17.78 [.700]	7	641244-7
15.24 [.600]	6	641244-6
12.70 [.500]	5	641244-5
10.16 [.400]	4	641244-4
7.62 [.300]	3	641244-3
5.08 [.200]	2	641244-2
DIM A	NO.OF POSN	ASSEMBLY

7 SUPERCEDED
 7 CONTAINS LEAD

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN S. HOOVER 28-DEC-2004	TE Connectivity
0 PLC ±	1 PLC ±	28-DEC-2004	
2 PLC ±	3 PLC ±	APVD D. ROSSI 28-DEC-2004	NAME
4 PLC ±	ANGLES ±	PRODUCT SPEC	MTA .100 CONNECTOR ASSEMBLY, 28 AWG, STANDARD
		APPLICATION SPEC	SIZE
		114-1019	CAGE CODE
MATERIAL	FINISH	WEIGHT	DRAWING NO
		A1 00779	641244
		CUSTOMER DRAWING	RESTRICTED TO
		SCALE 6:1	SHEET 1 OF 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)