SPECIFICATION CONTROL DRAWING					SCD 55A0831	
Title	tle THREE CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, GENERAL PURPOSE, 600 VOLT					Revision D
	GENERAL PURPOSE, 600 VOLT 1-13-17 D   This specification sheet forms a part of the latest issue of Raychem Specification 55A. D					
СОМ	PONENT WIRES - 55A0811				·	
		CABLE CONST	RUCTION DE	TAILS		
	PART NUMBER <u>1</u> /	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)	
	55A0831-26-*	26	.086	.091	5.2	
	55A0831-24-*	24	.097	.102	7.0	
	55A0831-22-*	22	.108	.112	9.8	
	55A0831-20-*	20	.125	.130	14.4	
	55A0831-18-*	18	.151	.158	22.0	
	55A0831-16-*	16	.166	.173	27.5	
	55A0831-14-*	14	.203	.210	42.2	
	55A0831-12-*	12	.240	.246	62.7	
	55A0831-10-*	10	.240	.298	99.1	
	55A0831-8-*	8	.421	.438	185.	
	55A0831-6-*	6	.521	.542	289.	
	55A0831-4-*	4	.670	.691	459.	
CABLE RATINGS AND ADDITIONAL REQUIREMENTS     TEMPERATURE RATING: 150°C     Maximum continuous conductor temperature     VOLTAGE RATING: 600 volts (rms) at sea level     DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz     INSULATION FLAWS:     Spark Test, 5.7 kV (rms) at 3 kHz     Impulse Dielectric Test, 8.0 kV (peak)         (PART NUMBER: The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors. Colors shown do not necessarily reflect the sequence of manufacturing.      Example:   AWG 22, orange, blue, and white component wires: 55A0831-22-3/6/9						e separating the e do not anufacturing.
Tyco Electroni <u>1</u> / COLORS ANI AN ALTERNA	E: Nominal values are for information Users should evaluate the suitabil cs Corporation also reserves the right to make o D COLOR CODE DESIGNATORS SHALL BE IN AC TIVE COLOR CODE MAY REPLACE MIL-STD-68 AY BE ADDED TO THE PART NUMBER, AS NECE	ity of this product for thei hanges in materials or p CORDANCE WITH MIL-S I COLOR CODE DESIGN/	r application. Spe rocessing, which TD-681. HOWEVE ATORS. (EXAMPL	ecifications are sub do not affect comp ER, DUE TO LENGT E: "901/902" MA <sup>\</sup>	liance with any specific TH LIMITATIONS OF THI ( BE REPLACED BY "Ax	E RAYCHEM PART NUMBER, xxx <sup>°</sup> .) OTHER CODES AND
	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.					Raychem Wire & Cable
Page 1 of 1	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL				5	501 Oakside Avenue Redwood City, CA 94063-3800
	THIS SPECIFICATION SHEFT TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN					Phone: 1-800-522-6752 Fax: 1-650-361-6297

© 2009-2017 Tyco Electronics Corporation. All rights reserved.

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)