



REVISIONS					
P	LTR	DESCRIPTION	DATE	DN	APVD
K		PLASTIC MATERIAL SUPPLIER CHANGED FOR HOUSING	06MAY2021	SB	KJK

- 1 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 2 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- 3 TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- 4 FINISH: POSTS, .000030 GOLD IN CONTACT AREA, .000100-.000200 MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER .000050 NICKEL.
- 5 FINISH: POSTS, .000030 GOLD IN CONTACT AREA, .000100-.000200 MATTE TIN ON SOLDER TAIL, ALL OVER .000050 NICKEL.
- 6 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



RECOMMENDED HOLE LAYOUT

PLATING	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER
OBSOLETE	3.984	3.900	39	80	8-103542-9
OBSOLETE	3.284	3.200	32	66	8-103542-2
OBSOLETE	2.984	2.900	29	60	7-103542-9
OBSOLETE	2.484	2.400	24	50	7-103542-4
OBSOLETE	2.284	2.200	22	46	7-103542-2
OBSOLETE	2.084	2.000	20	42	7-103542-0
OBSOLETE	1.984	1.900	19	40	6-103542-9
OBSOLETE	1.884	1.800	18	38	6-103542-8
OBSOLETE	1.784	1.700	17	36	6-103542-7
OBSOLETE	1.684	1.600	16	34	6-103542-6
OBSOLETE	1.584	1.500	15	32	6-103542-5
OBSOLETE	1.484	1.400	14	30	6-103542-4
OBSOLETE	1.384	1.300	13	28	6-103542-3
OBSOLETE	1.284	1.200	12	26	6-103542-2
OBSOLETE	1.184	1.100	11	24	6-103542-1
OBSOLETE	1.084	1.000	10	22	6-103542-0
OBSOLETE	.984	.900	9	20	5-103542-9
OBSOLETE	.884	.800	8	18	5-103542-8
OBSOLETE	.784	.700	7	16	5-103542-7
OBSOLETE	.684	.600	6	14	5-103542-6
OBSOLETE	.584	.500	5	12	5-103542-5
OBSOLETE	.484	.400	4	10	5-103542-4
OBSOLETE	.384	.300	3	8	5-103542-3
OBSOLETE	.284	.200	2	6	5-103542-2
OBSOLETE	.184	.100	1	4	5-103542-1

OBSOLETE	3.984	3.900	39	80	3-103542-9
OBSOLETE	3.884	3.800	38	78	3-103542-8
OBSOLETE	3.784	3.700	37	76	3-103542-7
OBSOLETE	3.684	3.600	36	74	3-103542-6
OBSOLETE	3.584	3.500	35	72	3-103542-5
OBSOLETE	3.484	3.400	34	70	3-103542-4
OBSOLETE	3.384	3.300	33	68	3-103542-3
OBSOLETE	3.284	3.200	32	66	3-103542-2
OBSOLETE	3.184	3.100	31	64	3-103542-1
OBSOLETE	3.084	3.000	30	62	3-103542-0
OBSOLETE	2.984	2.900	29	60	2-103542-9
OBSOLETE	2.884	2.800	28	58	2-103542-8
OBSOLETE	2.784	2.700	27	56	2-103542-7
OBSOLETE	2.684	2.600	26	54	2-103542-6
OBSOLETE	2.584	2.500	25	52	2-103542-5
OBSOLETE	2.484	2.400	24	50	2-103542-4
OBSOLETE	2.384	2.300	23	48	2-103542-3
OBSOLETE	2.284	2.200	22	46	2-103542-2
OBSOLETE	2.184	2.100	21	44	2-103542-1
OBSOLETE	2.084	2.000	20	42	2-103542-0
OBSOLETE	1.984	1.900	19	40	1-103542-9
OBSOLETE	1.884	1.800	18	38	1-103542-8
OBSOLETE	1.784	1.700	17	36	1-103542-7
OBSOLETE	1.684	1.600	16	34	1-103542-6
OBSOLETE	1.584	1.500	15	32	1-103542-5
OBSOLETE	1.484	1.400	14	30	1-103542-4
OBSOLETE	1.384	1.300	13	28	1-103542-3
OBSOLETE	1.284	1.200	12	26	1-103542-2
OBSOLETE	1.184	1.100	11	24	1-103542-1
OBSOLETE	1.084	1.000	10	22	1-103542-0
OBSOLETE	.984	.900	9	20	103542-9
OBSOLETE	.884	.800	8	18	103542-8
OBSOLETE	.784	.700	7	16	103542-7
OBSOLETE	.684	.600	6	14	103542-6
OBSOLETE	.584	.500	5	12	103542-5
OBSOLETE	.484	.400	4	10	103542-4
OBSOLETE	.384	.300	3	8	103542-3
OBSOLETE	.284	.200	2	6	103542-2
OBSOLETE	.184	.100	1	4	103542-1

6 SUPERSEDED BY 5-103542-3

THIS DRAWING IS A CONTROLLED DOCUMENT. **STE** TE Connectivity

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN H. MOLL 23 JAN 91	APVD I. A. MAYER 23 JAN 91	NAME
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± .005	4 PLC ± -
ANGLES ± -				
MATERIAL	FINISH SEE TABLE	WEIGHT	SIZE CAGE CODE DRAWING NO	RESTRICTED TO
			A1 00779 C=103542	
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 of 1	REV K

HDR ASSY, MOD II, UNSHRD, COMP PIN, DR .100 X .100 C/L, .025 SQ POSTS

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)