



- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS.
- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- FINISH: 0.000127 [.000005] GOLD IN CONTACT AREA, 0.00254-0.00508 [.000100-.000200] TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.
- OBsolete PARTS: OBsolete CIS STREAMLINING PER D.RENAUD/D.SINISI

5	OBsolete	101.19 [3.984]	99.06 [3.900]	39	80	4-146443-0
		98.65 [3.884]	96.52 [3.800]	38	78	3-146443-9
		96.11 [3.784]	93.98 [3.700]	37	76	3-146443-8
		93.57 [3.684]	91.44 [3.600]	36	74	3-146443-7
		91.03 [3.584]	88.90 [3.500]	35	72	3-146443-6
		88.49 [3.484]	86.36 [3.400]	34	70	3-146443-5
		85.95 [3.384]	83.82 [3.300]	33	68	3-146443-4
		83.41 [3.284]	81.28 [3.200]	32	66	3-146443-3
		80.87 [3.184]	78.74 [3.100]	31	64	3-146443-2
		78.33 [3.084]	76.20 [3.000]	30	62	3-146443-1
75.79 [2.984]	73.66 [2.900]	29	60	3-146443-0		
73.25 [2.884]	71.12 [2.800]	28	58	2-146443-9		
70.71 [2.784]	68.58 [2.700]	27	56	2-146443-8		
68.17 [2.684]	66.04 [2.600]	26	54	2-146443-7		
65.63 [2.584]	63.5 [2.500]	25	52	2-146443-6		
63.09 [2.484]	60.96 [2.400]	24	50	2-146443-5		
60.55 [2.384]	58.42 [2.300]	23	48	2-146443-4		
58.01 [2.284]	55.88 [2.200]	22	46	2-146443-3		
55.47 [2.184]	53.34 [2.100]	21	44	2-146443-2		
52.93 [2.084]	50.80 [2.000]	20	42	2-146443-1		
50.39 [1.984]	48.26 [1.900]	19	40	2-146443-0		
47.85 [1.884]	45.72 [1.800]	18	38	1-146443-9		
45.31 [1.784]	43.18 [1.700]	17	36	1-146443-8		
42.77 [1.684]	40.64 [1.600]	16	34	1-146443-7		
40.23 [1.584]	38.10 [1.500]	15	32	1-146443-6		
37.69 [1.484]	35.56 [1.400]	14	30	1-146443-5		
5	SUPERSEDED	35.15 [1.384]	33.02 [1.300]	13	28	1-146443-4
5	SUPERSEDED	32.61 [1.284]	30.48 [1.200]	12	26	1-146443-3
5	OBsolete	30.07 [1.184]	27.94 [1.100]	11	24	1-146443-2
5	OBsolete	27.53 [1.084]	25.40 [1.000]	10	22	1-146443-1
5	OBsolete	24.99 [.984]	22.86 [.900]	9	20	1-146443-0
5	OBsolete	22.45 [.884]	20.32 [.800]	8	18	146443-9
5	OBsolete	19.91 [.784]	17.78 [.700]	7	16	146443-8
5	OBsolete	17.37 [.684]	15.24 [.600]	6	14	146443-7
5	OBsolete	14.83 [.584]	12.70 [.500]	5	12	146443-6
5	OBsolete	12.29 [.484]	10.16 [.400]	4	10	146443-5
5	SUPERSEDED	9.75 [.384]	7.62 [.300]	3	8	146443-4
5	OBsolete	7.21 [.284]	5.08 [.200]	2	6	146443-3
5	OBsolete	4.67 [.184]	2.54 [.100]	1	4	146443-2
5	OBsolete	2.13 [.084]	- [-]	0	2	146443-1
		C	B	A	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0 PLC ± -	1 PLC ± -	2 PLC ± 0.51[.02]	3 PLC ± 0.127[.005]	4 PLC ± 0.0127[.0005]	ANGLES ± -
MATERIAL: POST: COPPER ALLOY	FINISH: 4	DRN: I. HOFFMAN	9/19/95	CHK: G. DUBNICZKI	9/20/95	APVO: G. DUBNICZKI	9/20/95
WEIGHT: -		SIZE: A1		CAGE CODE: 00779		DRAWING NO: 146443	
CUSTOMER DRAWING		SCALE: 4:1		SHEET: 1 OF 1		REV: D	

STE TE Connectivity
 HEADER ASSEMBLY, MOD II, BREAKAWAY, DOUBLE ROW, .100 X .100 CL, VERTICAL, .025 SQ. POST

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)