





ELECTRICAL PROPERTIES	
CURRENT RATING	1 AMP
INSULATION RESISTANCE	>5 x 10 ⁹ OHMS @ 500 VDC
DWV	>1000 VRMS AT SEA LEVEL
ENVIRONMENTAL PROPERTIES	
TEMPERATURE RATING	-55°C TO 125°C

REVISONS		DATE	BY	APPV
P	LTR			
C	REVISED PER ECO-09-026142	19FEB2010	CR	CR

- 20 POSITION ASSEMBLY SHOWN.
- HOUSING AND COVER: GLASS REINFORCED POLYESTER, UL94V-0 RATED, COLOR BLUE.
- CONTACTS: BERYLLIUM COPPER.
- CONTACTS: 0.00254[.000100] MIN TIN-LEAD OVER 0.00127[.000050] MIN NICKEL.
- NOTCHES MAY OR MAY NOT BE PRESENT ALONG EDGES OF COVER OR HOUSING.
- OBSOLETE



SUPERSEDED	2.54 [.100]	78.74 [3.100]	31	86.51 [3.406]	64	622-6453	1437008-6
SUPERSEDED	2.54 [.100]	73.66 [2.900]	29	81.43 [3.206]	60	622-6053	9-1437007-9
SUPERSEDED	2.54 [.100]	60.96 [2.400]	24	68.73 [2.706]	50	622-5053	8-1437007-9
OBSOLETE	2.54 [.100]	53.34 [2.100]	21	61.11 [2.406]	44	622-4453	8-1437007-5
SUPERSEDED	2.54 [.100]	48.26 [1.900]	19	56.03 [2.206]	40	622-4053	7-1437007-7
	2.54 [.100]	43.18 [1.700]	17	50.95 [2.006]	36	622-3653	7-1437007-3
SUPERSEDED	2.54 [.100]	40.64 [1.600]	16	48.41 [1.906]	34	622-3453	6-1437007-5
OBSOLETE	2.54 [.100]	35.56 [1.400]	14	43.33 [1.706]	30	622-3053	6-1437007-0
SUPERSEDED	2.54 [.100]	30.48 [1.200]	12	38.25 [1.506]	26	622-2653	5-1437007-1
SUPERSEDED	2.54 [.100]	27.94 [1.100]	11	35.71 [1.406]	24	622-2453	4-1437007-4
SUPERSEDED	2.54 [.100]	22.86 [.900]	9	30.63 [1.206]	20	622-2053	3-1437007-7
SUPERSEDED	2.54 [.100]	17.78 [.700]	7	25.55 [1.006]	16	622-1653	2-1437007-9
SUPERSEDED	2.54 [.100]	15.24 [.600]	6	23.01 [.906]	14	622-1453	2-1437007-0
SUPERSEDED	2.54 [.100]	10.16 [.400]	4	17.93 [.706]	10	622-1053	1-1437007-2
SUPERSEDED	2.54 [.100]	7.62 [.300]	3	15.39 [.606]	8	622-0853	1437007-8
	3.96 [.156]	5.08 [.200]	2	12.85 [.506]	6	622-0663	1437007-6
SUPERSEDED	2.54 [.100]	5.08 [.200]	2	12.85 [.506]	6	622-0653	1437007-5

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES. TOLERANCES UNLESS OTHERWISE SPECIFIED: 0. PLC ±, 1. PLC ±, 2. PLC ±, 3. PLC ±, 4. PLC ±, ANGLES ±.

MATERIAL: FINISH.

APPROVED: J. GERACE, C. ROHDE, M. WALMSLEY.

NAME: Tyco Electronics Corporation, Harrisburg, PA 17105-3608.

PRODUCT SPEC: CONNECTOR ASSEMBLY, SLIMLINE PCB.

APPLICATION SPEC.

SIZE: A1. CAGE CODE: 00779. DRAWING NO: 1437007-5.

RESTRICTED TO: CUSTOMER DRAWING. SCALE: 5:1. SHEET: 1 OF 1. REV: C.

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)