

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	15OCT2016	YC	CW
	B	ECR-21-111798	17SEP2021	WQR	CW



NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: CONDUCTOR-GROUND 400V  
CONDUCTOR-CONDUCTOR 690V  
RATED CURRENT: 40 A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 6 KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE: 1-6 mm<sup>2</sup> (18-10 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING:T20400X20XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 导体-地 400V; 导体-导体 690V  
额定电流: 40A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 6 KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
接线范围: 1-6 mm<sup>2</sup> (18-10 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20400X20XX000)

T2070032201-000	HM-003-F	HM-003 FEMALE INSERT HM-003 模块母插
PART NUMBER 料号	PART DESCRIPTION 描述	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	15OCT2016	 TE Connectivity
		CHK	15OCT2016	
		APVD	15OCT2016	
		NAME	CHRIS WANG	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME HM-003-F
		0 PLC	±-	PRODUCT SPEC
		1 PLC	±-	-
		2 PLC	±-	APPLICATION SPEC
		3 PLC	±-	-
		4 PLC	±-	WEIGHT
		ANGLES	±-	-
MATERIAL		FINISH	±-	SIZE
-		-	-	A3
-		-	-	CAGE CODE
				00779
				DRAWING NO
				T2070032201000
				RESTRICTED TO
				-
				CUSTOMER DRAWING
				SCALE
				3:2
				SHEET
				1 OF 1
				REV
				B

1470-19 (3/13)

Downloaded From [Onevac.com](http://Onevac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)