

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION .19
 © COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS					
P	LTR	DESCRIPTION	ECN	DATE	DWN	APVD			
0		作成 RELEASED	FJ00-0158-98	30 JAN 98	ES				

NOTE,

- 1 APPLICABLE P.C.BOARD THICKNESS: 1.6mm
- 2 RECOMMENDED MOUNTING SCREW: 4mmDIA, 6mmLENGTH
TAPPING SCREW SPECIFIED IN JIS B1115, B1122
(TIGHTENING TORQUE: 4kgcm MAX)
- 3 THE MATING PLUG HSG P/N; 353112,1123632

注:

- 1 通用プリント基板厚: 1.6mm
- 2 推奨取付ネジ: JIS B1115, B1122 タッピンネジ, ナベ 2種
呼び径 4, 長さ 6mm (締付トルク 4kgcm以下)
- 3 嵌合相手型番; 353112, 1123632

推奨プリント基板取付け寸法 (公差 ±0.1)
 (MOUNTING DIMENSIONS FOR P.C. BOARD; TOLERANCE ±0.1)
 ピッチ公差は累積しないこと (NON ACCUMULATE PITCH TOLERANCE)

緑 (GREEN)	1123630-4
色 (COLOR)	型番 (P/N)

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		OWN CHK E. Sasaki 30 JAN 98	AMP 日本エー・エム・ピー株式会社 Kawasaki, Japan	
DIMENSIONS: 単位 純 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD 2. H. Sasaki	NAME .04011 SRS MULTI-LOCK CONN. MK-II 48Pos. CAP ASSY	RESTRICTED TO ---
MATERIAL 材料 HOUSING : PBT ハウジング : PBT CONTACT : BRASS コンタクト : 黄銅	FINISH 仕上 PRE-TIN 錫めつき済	PRODUCT SPEC 製品仕様 108-5452	PRODUCT SPEC 製品仕様 .04011 シリーズ マルチロック コネクタ MK-II 48極 キャップハウジング アッセンブリ	SIZE A2
		APPLICATION SPEC 取付適用仕様	APPLICATION SPEC 取付適用仕様	CAGE CODE 00779
WEIGHT 16.8g		DRAWING NO 1123630		SCALE 2-1
CUSTOMER DRAWING		SHEET 1 OF 1		REV 0

AMP 1471-9 REV 10/93 Downloaded From Onevac.com

参考図面

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)