

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	D	REV PER ECO 19-019307	3-6-20	CT PD

- MATERIAL:
 BODY: ALUMINUM PER ASTM B317
 INSERT: BRASS PER ASTM B36
- FINISH:
 BODY: .000600 MIN MATTE TIN PER ASTM B545
 OVER .000060 MIN NICKEL PER ASTM B733.
 INSERT: .000150 MIN MATTE NICKEL PER QQ-N-290
- PTFE DRY LUBRICANT 360 DEGREE ON OUTER DIAMETER OF CRIMP BARREL IN ZONE SHOWN.
- WIRE INSULATION RANGE: .425-.513.
- SEE TE CONNECTIVITY APPLICATION SPEC. 114-32098 FOR APPLICATION REQUIREMENTS.
- SEE TE CONNECTIVITY INSTRUCTION SHEET 408-32087 FOR TOOLING AND CRIMP INSTRUCTIONS, FIGURE 3 FOR WIRE STRIPPING DETAIL.

3.390 MAX
 LUBRICANT APPLICATION ZONE
 2X Ø .390
 .807 + .005 / - .010
 .440 MIN
 1.000 ± .010
 .340 ± .020

Ø .530 ± .002
 .250 REF
 INSERT
 Ø .690 MAX
 1.187 MIN
 Ø .444 MIN WIRE ENTRY
 .190 MAX
 .005
 SECTION X-X
 TERMINAL BODY

2102580-1
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Brent D. Yohn 07APR2014	TE Connectivity	
DIMENSIONS: IN		CHK K. A. DeBock 07APR2014		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD K. A. DeBock 07APR2014	NAME TERMINAL ASSEMBLY ALUMINUM, SRAIGHT, DUAL HOLE SIZE 1/0	
0 PLC ± 1 PLC ± 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0005 ANGLES ±1		PRODUCT SPEC -	SIZE CAGE CODE DRAWING NO A200779 C-2102580	
MATERIAL SEE CALL-OUT		FINISH SEE-CALL-OUT	RESTRICTED TO	
WEIGHT 25.38GRAMS		CUSTOMER DRAWING		SCALE 3:1 SHEET 1 OF 1 REV D

1471-9 (3/11)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)