



- 1 HOUSING: FLAME RETARDANT, GLASS FILLED, POLYESTER, COLOR: BLACK. CONTACT: PHOSPHOR BRONZE
- 2 CONTACT: DUPLEX PLATED 0.25µm[.000010] MIN GOLD IN CONTACT AREA, 3.81-7.62µm[.000150-.000300] BRIGHT TIN-LEAD ON LEADS, ALL OVER 1.27µm[.000050] NICKEL
- 3 THESE DIMENSIONS PERTAIN TO CAVITY CENTERLINES ONLY - NOT TO CONTACT LOCATIONS
- 4 MARK PART NUMBER AND DATE CODE IN APPROXIMATE LOCATION SHOWN, EITHER SIDE.
- 5 TOLERANCE IS NON-CUMULATIVE.
- 6 2 POSITION DATE CODE IS MARKED OPPOSITE SIDE OF TE CONNECTIVITY LOGO.
- 7 POINT-OF-MEASUREMENT DIMENSION FOR PLATING THICKNESS (INSIDE CONTACT BEAM).
- 8 POINT-OF-CONTACT DIMENSION.
- 9 TE CONNECTIVITY TRADEMARK AND CSA LOGO ARE MOLDED INTO HOUSING, THIS LOCATION.
- 10 NO PART NUMBER MARKING REQUIRED FOR THIS PART.
- 11 CONTACT: DUPLEX PLATED 0.25µm[.000010] MIN GOLD IN CONTACT AREA, 3.81-7.62µm[.000150-.000300] MATTE TIN ON LEADS, ALL OVER 1.27µm[.000050] MIN NICKEL
- 12 ROHS 2002/95/EC COMPLIANT.

LOC	DIST	P	LTR	REVISED	PER	ECO	DATE	DMN	APVD
12	11			96.52[3.800]		99.06[3.900]	78		9-535598-0
12	11			93.98[3.700]		96.52[3.800]	76		8-535598-9
12	11			91.44[3.600]		93.98[3.700]	74		8-535598-8
12	11			88.90[3.500]		91.44[3.600]	72		8-535598-7
12	11			86.36[3.400]		88.90[3.500]	70		8-535598-6
12	11			83.82[3.300]		86.36[3.400]	68		8-535598-5
12	11			81.28[3.200]		83.82[3.300]	66		8-535598-4
12	11			78.74[3.100]		81.28[3.200]	64		8-535598-3
12	11			76.20[3.000]		78.74[3.100]	62		8-535598-2
12	11			71.12[2.800]		73.66[2.900]	58		8-535598-1
12	11			68.58[2.700]		71.12[2.800]	56		8-535598-0
12	11			66.04[2.600]		68.58[2.700]	54		7-535598-9
12	11			63.50[2.500]		66.04[2.600]	52		7-535598-8
12	11			58.42[2.300]		60.96[2.400]	48		7-535598-7
12	11			55.88[2.200]		58.42[2.300]	46		7-535598-6
12	11			53.34[2.100]		55.88[2.200]	44		7-535598-5
12	11			50.80[2.000]		53.34[2.100]	42		7-535598-4
12	11			99.06[3.900]		101.60[4.000]	80		7-535598-3
12	11			73.66[2.900]		76.20[3.000]	60		7-535598-2
12	11			60.96[2.400]		63.50[2.500]	50		7-535598-1
12	11			48.26[1.900]		50.80[2.000]	40		7-535598-0
12	11			45.72[1.800]		48.26[1.900]	38		6-535598-9
12	11			43.18[1.700]		45.72[1.800]	36		6-535598-8
12	11			40.64[1.600]		43.18[1.700]	34		6-535598-7
12	11			38.10[1.500]		40.64[1.600]	32		6-535598-6
12	11			35.56[1.400]		38.10[1.500]	30		6-535598-5
12	11			33.02[1.300]		35.56[1.400]	28		6-535598-4
12	11			30.48[1.200]		33.02[1.300]	26		6-535598-3
12	11			27.94[1.100]		30.48[1.200]	24		6-535598-2
12	11			25.40[1.000]		27.94[1.100]	22		6-535598-1
12	11			22.86[.900]		25.40[1.000]	20		6-535598-0
12	11			20.32[.800]		22.86[.900]	18		5-535598-9
12	11			17.78[.700]		20.32[.800]	16		5-535598-8
12	11			12.70[.500]		15.24[.600]	12		5-535598-7
12	11			10.16[.400]		12.70[.500]	10		5-535598-6
12	11			7.62[.300]		10.16[.400]	8		5-535598-5
12	11			5.08[.200]		7.62[.300]	6		5-535598-4
12	11			2.54[.100]		5.08[.200]	4		5-535598-3
12	11	10				2.54[.100]	2		5-535598-2
12	11			15.24[.600]		17.78[.700]	14		5-535598-1
2				96.52[3.800]		99.06[3.900]	78		4-535598-0
2				93.98[3.700]		96.52[3.800]	76		3-535598-9
2				91.44[3.600]		93.98[3.700]	74		3-535598-8
2				88.90[3.500]		91.44[3.600]	72		3-535598-7
2				86.36[3.400]		88.90[3.500]	70		3-535598-6
2				83.82[3.300]		86.36[3.400]	68		3-535598-5
2				81.28[3.200]		83.82[3.300]	66		3-535598-4
2				78.74[3.100]		81.28[3.200]	64		3-535598-3
2				76.20[3.000]		78.74[3.100]	62		3-535598-2
2				71.12[2.800]		73.66[2.900]	58		3-535598-1
2				68.58[2.700]		71.12[2.800]	56		3-535598-0
2				66.04[2.600]		68.58[2.700]	54		2-535598-9
2				63.50[2.500]		66.04[2.600]	52		2-535598-8
2				58.42[2.300]		60.96[2.400]	48		2-535598-7
2				55.88[2.200]		58.42[2.300]	46		2-535598-6
2				53.34[2.100]		55.88[2.200]	44		2-535598-5
2				50.80[2.000]		53.34[2.100]	42		2-535598-4
2				99.06[3.900]		101.60[4.000]	80		2-535598-3
2				73.66[2.900]		76.20[3.000]	60		2-535598-2
2				60.96[2.400]		63.50[2.500]	50		2-535598-1
2				48.26[1.900]		50.80[2.000]	40		2-535598-0
2				45.72[1.800]		48.26[1.900]	38		1-535598-9
2				43.18[1.700]		45.72[1.800]	36		1-535598-8
2				40.64[1.600]		43.18[1.700]	34		1-535598-7
2				38.10[1.500]		40.64[1.600]	32		1-535598-6
2				35.56[1.400]		38.10[1.500]	30		1-535598-5
2				33.02[1.300]		35.56[1.400]	28		1-535598-4
2				30.48[1.200]		33.02[1.300]	26		1-535598-3
2				27.94[1.100]		30.48[1.200]	24		1-535598-2
2				25.40[1.000]		27.94[1.100]	22		1-535598-1
2				22.86[.900]		25.40[1.000]	20		1-535598-0
2				20.32[.800]		22.86[.900]	18		535598-9
2				17.78[.700]		20.32[.800]	16		535598-8
2				12.70[.500]		15.24[.600]	12		535598-7
2	10			10.16[.400]		12.70[.500]	10		535598-6
2	10			7.62[.300]		10.16[.400]	8		535598-5
2	10			5.08[.200]		7.62[.300]	6		535598-4
2	10			2.54[.100]		5.08[.200]	4		535598-3
2	10					2.54[.100]	2		535598-2
2				15.24[.600]		17.78[.700]	14		535598-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN M. BINNER 06NOV2002	TE Connectivity
0 PLC ± -	1 PLC ± -	2 PLC ± 0.13[.005]	3 PLC ± -
4 PLC ± -	ANGLES ± -	APVD J. JOLSON 06NOV02	NAME
MATERIAL 1	FINISH 2	PRODUCT SPEC J. JOLSON 06NOV02	RECEPTACLE ASSEMBLY, MOD IV, DOUBLE ROW, DUAL ENTRY, .100X.100CL, VERTICAL MOUNT, AMPMODU
		APPLICATION SPEC 114-25018	SIZE CASE CODE DRAWING NO
		WEIGHT	A1 00779 535598
		CUSTOMER DRAWING	SCALE 1:1 SHEET 1 OF 1 REV P5

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)