



- 1 HOUSING: THERMOPLASTIC, BLACK, UL 94V-0 RATED.
SHELL: CARBON STEEL.
CONTACTS: PHOSPHOR BRONZE.
BRACKETS: NICKEL SILVER.
- 2 SHELL: 5.08µm MIN NICKEL OVER 2.54µm MIN COPPER.
CONTACTS: 0.76µm MIN GOLD ON MATING END, 3.75µm MIN TIN-LEAD ON SOLDER TAILS, BOTH OVER 1.27µm MIN NICKEL ON ENTIRE CONTACT.
- 3 BRACKETS AND CONTACTS DESIGNED FOR USE ON 1.60±0.15 THICK PC BOARD WITH PLATED THRU MOUNTING HOLES.
- 4 RECEPTACLE ASSEMBLY DESIGNED FOR USE WITH 1.12±0.08 THICK PANEL.
- 5 DATUMS AND DIMENSIONS ESTABLISHED BY CUSTOMER.
- 6 POSITION TOLERANCE APPLIES AT CONTACT TIP ONLY.
- 7 MAXIMUM TORQUE 0.45 N-M.
- 8 DATE CODE MARKED IN APPROXIMATE AREA SHOWN.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. SHUEY	09MAR05		Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm		CHK J. GERACE	09MAR05		NAME M. WALMSLEY	RECEPTACLE ASSEMBLY, 36 POSITION, SHIELDED, RIGHT ANGLE, CHAMP 0.8mm
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		APPLICATION SPEC		
0 PLC ± -		1 PLC ± ±		108-1471-1		
1 PLC ± ±		2 PLC ± ± 0.13		114-6057		
2 PLC ± ±		3 PLC ± ±		SIZE A1		
3 PLC ± ±		4 PLC ± ±		CASE CODE 00779		
4 PLC ± ±		ANGLES ± 1°		DRAWING NO. 787973		
MATERIAL		FINISH		WEIGHT		
1		2		CUSTOMER DRAWING		
				SCALE 8:1		
				SHEET 1 of 1		
				REV L		

787973-1
PART NUMBER

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)