

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

REVISIONS

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	25FEB2015	GY	CW
	B	ECR-15-017607	03DEC2015	GY	CW
	C	ECR-21-117384	05NOV2021	WQR	CW

6 X M4 thread, recommended tightening torque 1.2Nm

M4 thread, recommended tightening torque 1.2Nm

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 INSULATION MATERIAL: PC(Gray)  
 RATED VOLTAGE: CONDUCTOR-GROUND: 400V  
 CONDUCTOR-CONDUCTOR: 690V  
 RATED CURRENT: 35A  
 INSULATION RESISTANCE:  $\geq 400M\Omega$   
 RATED IMPULSE VOLTAGE: 6KV  
 POLLUTION DEGREE: 3  
 CONTACT RESISTANCE:  $\leq 5m\Omega$   
 FLAMMABILITY: UL94V-0  
 MATING CYCLES: 500  
 OPERATION TEMPERATURE:  $-40^{\circ}C \sim +125^{\circ}C$   
 WIRE RANGE:  $1.5mm^2 \sim 6.0mm^2$  (AWG16-AWG10)  
 CONTACT FINISH: SILVER PLATED  
 CONTACT TYPE: SCREW CLAMP (M4)

4 X M3 thread, recommended tightening torque 0.5Nm

注释:

1. 技术参数:  
 绝缘材料: PC(Gray)  
 额定电压: 导体-地: 400V  
 导体-导体: 690V  
 额定电流: 35A  
 绝缘电阻:  $\geq 400M\Omega$   
 脉冲电压: 6KV  
 污染等级: 3  
 接触电阻:  $\leq 5 m\Omega$   
 阻燃等级: UL94V-0  
 插拔次数: 500  
 工作温度:  $-40^{\circ}C \sim +125^{\circ}C$   
 接线范围:  $1.5mm^2 \sim 6.0mm^2$  (AWG16-AWG10)  
 端子表面处理: 镀银  
 接线类型: 螺丝压接 (M4)

Panel cut out for inserts for using without hoods/housings

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	Gino.Yao	10Dec2014	 TE Connectivity	NAME	HSB-006-F									
DIMENSIONS:		CHK	Chris.Wang	10Dec2014			PRODUCT SPEC	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO					
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	Xiang.Xu	10Dec2014								APPLICATION SPEC	SCALE	SHEET	OF	REV
mm		PRODUCT SPEC	108-137052													
MATERIAL		FINISH		WEIGHT		Customer Drawing		1:1	1 OF 1	C						

1470-19 (3/13)

Downloaded From [Onevac.com](http://Onevac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)