

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
D		REVISED PER ECO-17-002903	20MAR2017	AP DG

1 PLUG ACCEPTS 22 DF PIN CONTACTS. CONTACTS MUST BE PURCHASED SEPARATELY.
 2 ALL PARTS SHIPPED UNASSEMBLED, EACH PART INDIVIDUALLY BULK PACKED.
 3 FLAME RETARDANT 94V-0 RATED, STYRENE POLYOLEFIN OR PVC, BLACK.
 4 FLAME RETARDANT 94V-0 RATED, GLASS FILLED NYLON OR POLYESTER, BLACK.
 5 CARBON STEEL.
 6 .000200 MIN TIN PLATE OVER .000100 MIN. COPPER UNDERPLATE.
 7 BLACK ZINC FLAKE COATING.
 8 CARBON STEEL, C1022.

EXPANDING NECK, ACCOMMODATES CABLE FROM .217-.435 DIA

2.210 MAX

FERRULE, MUST BE PURCHASED SEPARATELY, AS REQUIRED BY CABLE DIAMETER

4-40 JACKSCREW QTY: 2

SHIELD QTY: 2

ENCLOSURE

1.467 TYP

.812 TYP

.630 MAX

CABLE REF

.125 MAX

1.640 MAX

PLUG CONNECTOR
HDP-22

1.852

2	W/ LOGOS	1658680-1
PACKAGING	REMARKS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. BAUM 02JAN04		
DIMENSIONS: INCHES		CHK S. BOLASH 02JAN04		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. WALMSLEY 02JAN04	NAME	
0 PLC ± -		PRODUCT SPEC	SHIELDING ENCLOSURE KIT, PLUG, SIZE 3, 44 POSN, HDP-22, AMPLIMITE™	
1 PLC ± -		APPLICATION SPEC	SIZE CAGE CODE DRAWING NO RESTRICTED TO	
2 PLC ± -		108-1268	A2 00779 C=1658680	
3 PLC ± .005		114-10001	SCALE 2:1 SHEET 1 of 1 REV D	
4 PLC ± -		WEIGHT 0.000000		
ANGLES ± 2°		CUSTOMER DRAWING		
FINISH				
3 4 5 8				
6 7				

1471-9 (1/15)

Downloaded From Onevac.com

1658680

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)