

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

REVISIONS

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	20APR2015	GY	CW
	B	ECR-15-013759	12OCT2015	DW	CW
	C	ECR-21-106515	12JUL2021	SQ	CW

不使用防护外壳时芯件的安装开孔图
Panel cut out for inserts for use without hoods/housings

4 X M3 thread, recommended tightening torque 0.5Nm

M4 thread, recommended tightening torque 1.2Nm

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 500V
RATED CURRENT: 16A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 6KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40^{\circ}C \sim +125^{\circ}C$
WIRE RANGE: $0.14mm^2 \sim 4mm^2$ (AWG26-AWG12)
CONTACT TYPE: CRIMP CONTACT
- CONTACTS NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20300X10XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 500V
额定电流: 16A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 6KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40^{\circ}C \sim +125^{\circ}C$
接线范围: $0.14mm^2 \sim 4mm^2$ (AWG26-AWG12)
接线类型: 冷压接
- 端子需要单独订购。
(订货号参考图面: T20300X10XX000)

HE-016-MC 17-32	T2040324101-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	Gino.Yao	15APR2015	 TE Connectivity	NAME	HE-016-MC 17-32			
DIMENSIONS:		CHK	Chris.Wang	15APR2015			PRODUCT SPEC	108-137044		
mm		APVD	Xiang.Xu	15APR2015				APPLICATION SPEC	114-137044	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		MATERIAL					WEIGHT		SIZE	CAGE CODE
0 PLC	±-	-			-	A3	00779	T2040324101000	-	
1 PLC	±-	-			-	Customer Drawing			SCALE	
2 PLC	±-	-			-				1:1	
3 PLC	±-	-			-				SHEET	
4 PLC	±-	-			-				1 OF 1	
ANGLES	±-	-			-				REV	
FINISH	-	-			-				C	

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)