



RECOMMENDED PC BOARD MOUNTING DIMENSIONS FOR .063 [.160] THICK PC BOARD AND .012 [.305] STENCIL THICK.

- 1 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- 2 BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- 3 FOR ACTIVE POSITION SIZES 4 AND ABOVE, POSTS WILL BE SELECTIVELY SWAGED TO PROVIDE CONNECTOR RETENTION TO THE PC BOARD UNTIL SOLDERED. FOR POSITION SIZE 2, POSTS WILL BE KINKED.(SEE TABLE FOR RETENTION FEATURE LOCATION)
- 4 0.000381 [.000015] GOLD ON CONTACT AREA, 0.00254-0.00508 [.000100-.000200] MATTE TIN-LEAD ON SOLDER TAIL ALL OVER 0.00127 [.000050] NICKEL.
- 5 HOUSING: GLASS FILLED THERMOPLASTIC, COLOR, BLACK. (WILL WITHSTAND VAPOR PHASE REFLOW.) POST: COPPER ALLOY
- 6 0.000381 [.000015] GOLD ON CONTACT AREA, 0.00254-0.00508 [.000100-.000200] MATTE TIN ON SOLDER TAIL ALL OVER 0.00127 [.000050] NICKEL.
- 7 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. HOFFMAN 6-9-95	 TE Connectivity
DIMENSIONS: mm [INCHES]		CHK G. DUBNICZKI 12-9-95	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPV G. DUBNICZKI 12-9-95	NAME HEADER ASSEMBLY, MOD II, BREAKAWAY, HIGH TEMPERATURE, RIGHT ANGLE, DOUBLE ROW, .100 X.100CL W/.025 SQ POSTS WITH HOLD-DOWN CONFIGURATION.
0 PL ± - 1 PL ± - 2 PL ± 0.51[.02] 3 PL ± 0.12[.005] 4 PL ± 0.012[.0005] ANGLES ± -		PRODUCT SPEC	APPLICATION SPEC
MATERIAL		SIZE A1	WEIGHT
FINISH SEE TABLE		CAGE CODE 00779	DRAWING NO. 146427
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 OF 2

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)