



- △ POLYPHENYLENE SULFIDE.
- △ PHOSPHER BRONZE.
- △ DUPLEX PLATED: .000030 GOLD IN CONTACT AREA, .000050-.000100 BRIGHT TIN-LEAD ON LEADS, ALL OVER .000050 NICKEL.
- △ THESE DIMENSIONS PERTAIN TO CAVITY C'S ONLY, NOT TO CONTACT LOCATIONS.
- △ "AMP", "CSA", DATE CODE AND PART NUMBER MARKED WITH .062 ± .015 HIGH CHARACTERS. THE ORDER AND LOCATION ARE OPTIONAL.
- △ POINT-OF-MEASUREMENT FOR PLATING THICKNESS INSIDE BEAMS.
- 7. AVERAGE INSERTION FORCE IS 2.75 OUNCES OR LESS. MINIMUM WITHDRAW FORCE IS .50 OUNCE.
- △ DUPLEX PLATED: .000030 GOLD IN CONTACT AREA, .000050-.000100 MATTE TIN ON LEADS, ALL OVER .000050 NICKEL.
- △ ROHS 2002/95/EC COMPLIANT.

8	3.900	4.258	80	9	5-535681-1
3	3.900	4.258	80		535681-1
FINISH	B	A	NO. OF POSN	PART NO.	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN: FT. BOLES 4/29/93	CHK: J. PALEY 4/29/93	tyco Electronics	Tyco Electronics Corporation Harrisburg, PA 17105-3608
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± .005	4 PLC ± -	ANGLES ± -
FINISH SEE TABLE		PRODUCT SPEC		NAME	
		APPLICATION SPEC		ASSEMBLY, MOD II DOUBLE ROW. .100 X .100 CENTERLINE, VERTICAL MOUNTED LOW FORCE, SHORT POINT-OF-CONTACT	
		SIZE: A1	CAGE CODE: 00779	DRAWING NO: C=535681	RESTRICTED TO: -
		WEIGHT: -		CUSTOMER DRAWING	
		SCALE: 4:1		SHEET 1 OF 1 REV C1	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)