

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 2006  
 © COPYRIGHT 2006 BY TE CONNECTIVITY ALL RIGHTS RESERVED.

REVISIONS  
変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
B		REVISED PER ECR-10-007266	22APR2010	HMR	T.M
C		REVISED PER ECR-14-001037	24JAN2014	K.T	N.Y
D		REVISED PER ECR-16-015895	20NOV2016	K.T	E.T

1. MATERIAL: HOUSING: LIQUID CRYSTAL POLYMER  
 COLOR: BLACK  
 CONTACT: COPPER ALLOY  
 SOLDER PEG: BRASS

2. FINISH (ALL OVER): NICKEL PLATING 1.27μmMIN

3. FINISH (CONTACT AREA)  
 : GOLD PLATING 0.76μmMIN AFTER 2

4. FINISH (SOLDER PEG & CONTACT TAIL)  
 : TIN PLATING 2μmMIN AFTER 2

5. COPLANARITY 0.15mm MAX.  
 (CONTACT TINE AND SOLDER PEG ONLY)

6. THE SHAPE, SIZE AND POSITION OF THE CHARACTER  
 SHOW THE OUTLINE. THEY DON'T SHOW DETAILS.

7. THE KEYING ARRANGEMENT OF "Y" IS  
 SYMMETRIC WITH "X".

1. 材料: ハウジング: 液晶ポリマー、色: 黒  
 コンタクト: 銅合金  
 ソルダーペグ: 黄銅

2. めっき(全面): ニッケル下地めっき1.27μm以上

3. めっき(接触部): 2の上に金めっき0.76μm以上

4. めっき(ソルダーペグとコンタクト半田付部)  
 : 2の上に錫めっき2μm以上

5. コンタクトタイン部及びソルダーペグの  
 平面度(コプラナリティ)は0.15mmMAX

6. 文字の形状、大きさ、および位置等は、大略を示すものであり  
 詳細を示すものではありません。

7. Y KEY形状は、X KEY形状と左右対称

SCALE 1:1

REFERENCE PC BOARD PATTERN: CONNECTOR MOUNT SIDE  
 (NOT ACCUMULATE TOLERANCE)  
参考基板取付寸法: コネクタ搭載面(非累積公差)

	0.76μmMIN	40	Y	19	38.0	43.2	48.6	48.44	21.6	2-1939995-0
	0.76μmMIN	40	X	19	38.0	43.2	48.6	48.44	21.6	1-1939995-0
	0.76μmMIN	26	Y	12	24.0	29.2	34.6	34.44	14.6	2-1939995-3
	0.76μmMIN	26	X	12	24.0	29.2	34.6	34.44	14.6	1-1939995-3
OBSOLETE	0.38μmMIN	22	X	10	20.0	25.2	30.6	30.44	12.6	1-1939995-4
	GOLD	POS	KEY	n	A	B	C	D	E	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: 単位: 概 mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:  
 一般公差 ±0.3, ±3°  
 0-PLC ±  
 1-PLC ±  
 2-PLC ±  
 3-PLC ±  
 4-PLC ±  
 ANGLES ±

MATERIAL 材料 1

FINISH 仕上 2 3 4

DWN M. MAEBASHI 06NOV2006  
 CHK T. KUDO 06NOV2006  
 APVD D. MITSUGI 06NOV2006  
 PRODUCT SPEC 108-78414  
 APPLICATION SPEC 114-5405  
 WEIGHT

**TE** TE Connectivity

NAME 名称 DYNAMIC D1100D 2.0mmPITCH HDR ASSY, SMT/V-TYPE 22-40POS

SIZE A3 CAGE CODE 00779 DRAWING NO. 1939995 RESTRICTED TO

Customer Drawing SCALE 2:1 SHEET 1 OF 2 REV D

1470-19 (3/13)

Downloaded From [Onevac.com](http://Onevac.com)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2006

© COPYRIGHT 2006 BY -

ALL RIGHTS RESERVED.

REVISIONS

変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

Dimensions: C, B,  $2Xn=A$ , D REF (PEG)

26POS(X-KEY): 1-1939995-3

Part Number: D1100

Dimension: E

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

一般公差	±
0 PLC	±0.5
1 PLC	±0.13
2 PLC	±0.013
3 PLC	±0.001
4 PLC	±0.0001
ANGLES	±

MATERIAL  
材料  
TBDFINISH  
仕上

DWN 06NOV2006

M. MAEBASHI

CHK 06NOV2006

T. KUDO

APVD 06NOV2006

D. MITSUGI

PRODUCT SPEC

108-78414

APPLICATION SPEC

114-5405

WEIGHT

Customer Drawing

NAME  
名称DYNAMIC D1100D 2.0mmPITCH  
HDR ASSY, SMT/V-TYPE  
22-40POS

SIZE

A3

CAGE CODE

00779

DRAWING NO

C=1939995

RESTRICTED TO

-

TE Connectivity

1470-19 (3/13)

Downloaded From [Oneyc.com](http://Oneyc.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)