

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD		
	H	REV PER ECO 14-014240	10-1-14	CT	CD		

PIN BODY
 MAT'L: COPPER ALLOY
 FINISH: SEE TABLE

RETENTION CLIP
 MAT'L: BERYLLIUM COPPER OR PHOSPHOR BRONZE
 FINISH: NICKEL PLATED PER AMS-QQ-N-290

POINT OF PLATING THICKNESS MEASUREMENT

Dimensions:
 $\phi .067$ [1.70]
 $\phi .102$ [2.59]
 .360 [9.14]
 $.400 \pm .002$ [10.16 ± 0.05]
 $\phi .214$ [5.44]
 .080 MIN [2.03]
 .125 ± 0.010 [3.18 ± 0.25]
 .203 MIN [5.16]
 .860 REF [21.84]

- THIS PART CONFORMS TO REQUIREMENTS FOR DANIELS CRIMP TOOL NO. FT8, WITH DANIELS POSITIONER PART NO. TP731, STRIP LENGTH .375, #16 AWG SETTING 8, #18 AWG SETTING 6.
- MATES WITH 212013-1 IN AMPLIMITE CONNECTOR ASSEMBLIES ONLY.
- FINISH: PLATED GOLD .000050 [0.00127] MIN THK PER ATSM-B-488 OVER NICKEL .000050 [0.00127] MIN THK PER AMS-QQ-N-290.
- FINISH: PLATED GOLD .000030 [0.00076] MIN THK PER ATSM-B-488 OVER NICKEL .000050 [0.00127] MIN THK PER AMS-QQ-N-290.
- WIRE BARREL WILL ACCEPT #16-#18 AWG WIRE.
- PART NUMBER IS RESTRICTED.

PRELIMINARY NOT RELEASED FOR PRODUCTION	6	1-212014-1
	4	212014-2
	3	212014-1
FINISH	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	C.C.THOMAS	11/10/00		TE Connectivity			
DIMENSIONS: INCHES [mm]		CHK	D.MILLER	11/10/00		NAME			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	D.MILLER	11/10/00		ASSEMBLY, SOCKET CONTACT			
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 [0.13] 4 PLC ± - ANGLES ± -		PRODUCT SPEC	108-10045			POWER VIII, #16 & #18 AWG			
MATERIAL SEE CALLOUTS		FINISH	SEE TABLE		114-10014	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
		WEIGHT	-		114-10014	A2	00779	C=212014	-
		CUSTOMER DRAWING			SCALE	10:1	SHEET	1 of 1	REV
									H

1471-9 (3/11)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)