



- 1 MAXIMUM INSERTION LOSS IS 0.5 dB PLUS CABLE ATTENUATION OF 1.5 dB/km AT 1300 nm (SEE TABLE)
- 2 PRODUCT AND PROCESSING MUST MEET REQUIREMENTS OF STANDARD 230-702.

0.53	25.00±0.30 [984.0±12.0]	3-5504971-5
0.56	40.00±0.40 [1575.0±16.0]	3-5504971-4
0.73	150.00±1.50 [5906.0±59.0]	3-5504971-3
0.57	45.00±0.45 [1772.0±18.0]	3-5504971-2
0.50	2.43±0.05 [96.0±2.0]	3-5504971-1
0.50	1.82±0.05 [72.0±2.0]	3-5504971-0
0.50	1.21±0.05 [48.0±2.0]	2-5504971-9
0.52	10.97±0.15 [431.8±6.0]	2-5504971-8
0.52	10.36±0.15 [407.8±6.0]	2-5504971-7
0.51	9.75±0.15 [383.8±6.0]	2-5504971-6
0.51	9.14±0.15 [359.8±6.0]	2-5504971-5
0.51	8.53±0.15 [335.8±6.0]	2-5504971-4
0.51	7.92±0.15 [311.8±6.0]	2-5504971-3
0.59	60.0±0.60 [2362±24]	2-5504971-2
0.50	0.46±0.05 [18.00±2.00]	2-5504971-1
0.51	6.0±0.08 [236±3]	2-5504971-0
0.51	6.10±0.08 [240±3]	1-5504971-9
0.50	0.61±0.03 [24±1]	1-5504971-8
0.65	100±1.0 [3937±39]	1-5504971-7
0.58	50±0.5 [1969±20]	1-5504971-6
0.52	16±0.30 [630±12]	1-5504971-5
0.52	13±0.15 [512±6]	1-5504971-4
0.52	11±0.15 [433±6]	1-5504971-3
0.51	4±0.08 [157±3]	1-5504971-2
0.51	8±0.15 [315±6]	1-5504971-1
0.51	7±0.08 [275.6±3]	1-5504971-0
0.55	30±0.3 [1181±12]	5504971-9
0.53	20±0.3 [787±12]	5504971-8
0.52	15±0.15 [591±6]	5504971-7
0.61	76±0.76 [2992±30]	5504971-6
0.52	10±0.15 [394±6]	5504971-5
0.51	5±0.08 [197±3]	5504971-4
0.50	3±0.05 [118±2]	5504971-3
0.50	2±0.05 [79±2]	5504971-2
0.50	1±0.05 [39±2]	5504971-1
MAX IL (dB) $\Delta$	L	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		COMMSCOPE, INC.	
DMN	C.S.VASU	03 JAN 06	
CHK	J.DUNCAN	03 JAN 06	
AP'D	J.DUNCAN	03 JAN 06	
DIMENSIONS: METERS [INCHES]		NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CABLE ASSEMBLY, FIBER OPTIC, 3.0 mm	
0 PLG	±	62.5/125µm LDD ZIP, SC DUPLEX, OPTIMATE	
1 PLG	±		
2 PLG	±		
3 PLG	±		
4 PLG	±		
ANGLES	±		
FINISH	±		
MATERIAL	-	SIZE	A2
		QAGE CODE	00779
		DRAWING NO	5504971
		SCALE	NTS
		SHEET	1 of 1
		REV	B
		CUSTOMER DRAWING	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)