

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
CM	53	A	REVISED PER ECR-15-003328	03-30-15	SC KD

3-DIMENSIONAL MODEL
NTS

NOTES

1. TO BE USED WITH UNIVERSAL MATE-N-LOK2 PLUGS AND CAPS.
 ⚠ AMP LOGO LOCATION.

Technical drawing showing dimensions and features of the keying plug:

- Overall length: 23.37
- Left diameter: $\phi 2.49$
- Inner diameter (left): $\phi 1.65$
- Inner diameter (right): $\phi 1.78$
- Right diameter: $\phi 2.49$
- Feature: KNOCK-CUT MARKS (2)
- Feature: AMP LOGO LOCATION (indicated by a triangle symbol)

794369-1
PART NUMBER

MM	IN
23.37	.920
2.49	.098
1.78	.070
1.65	.065
0.13	.005
MM	IN

CONVERSION TABLE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. WHITAKER 5-21-97		
DIMENSIONS: mm		CHK R. SWING 5-21-97		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD R. ORSTAD 5-21-97	NAME KEYING PLUG, MINI UNIVERSAL MATE-N-LOK TM	
0 PLC ± -		PRODUCT SPEC 108-1693	SIZE A2	CAGE CODE 00779
1 PLC ± -		APPLICATION SPEC 114-1111	DRAWING NO C=794369	RESTRICTED TO -
2 PLC ± 0.13		WEIGHT -	SCALE 10:1	SHEET 1 of 1
3 PLC ± -		CUSTOMER DRAWING	REV A	
4 PLC ± -				
ANGLES ± 0° 30'				
FINISH -				
MATERIAL NYLON, UL 94V-0, NATURAL				

1471-9 (3/11)

Downloaded From Onevac.com

794369

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)