



1. THIS PLUG WILL MATE WITH ANY 104 POSN., SIZE 6 RECEPTACLE IN AMPLIMITE SERIES.
2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS PLUG IS .054 DIA.
3. SST RETENTION CLIPS ARE INCLUDED IN INSERTS.
4. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308.
5. CONNECTOR SUPPLIED WITHOUT CONTACTS.
6. THIS CONNECTOR WILL ACCEPT SIZE 22DF CONTACTS P/N 66556-3, 66718-4 OR SIZE 22DM CONTACTS P/N 204370-2 OR ANY OTHER SIZE 22 CONTACT IN THE AMPLIMITE SERIES.
7. TO INSTALL OR REMOVE CONTACTS USE INSERTION/EXTRACTION TOOL P/N 91067-1 OR MIL NUMBER M81969/1-04.

- 8 WITHOUT CLINCH NUTS; MOUNTING HOLE DIA .120
- 9 WITHOUT CUSTOMER PART NO.
- 10 FINISH: CADMIUM PER QQ-P-416
- 11 FINISH: PLATED CADMIUM PER QQ-P-416, YELLOW CHROMATE
- 12 NUT, CLINCH - IN ACCORDANCE WITH M45938/6-2 OR M45938/6-2C
- 13 NUT, CLINCH, 2-56 UNC - MATERIAL: CARBON STEEL FINISH: YELLOW CHROMATE OVER CADMIUM PER QQ-P-416
- 14 ZINC PLATE .000200 [0.0050] MIN. THICK PER ASTM-B-663, YELLOW CHROMATE.

SAME AS -1 EXCEPT: 8, 9, 10, 11, 12, 13, 14	212933-4
SAME AS -1 EXCEPT: 8, 9, 11, 12, 13, 14	212933-3
SAME AS -1 EXCEPT: 8, 9, 10, 11, 12, 13, 14	212933-2
AS SHOWN 8, 9, 10, 11, 12, 13, 14	212933-1
DESCRIPTION	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN	D.D.ERDMAN	5-31-85		Tyco Electronics Corporation
CHK	J.L.BROSCHARD	5-31-85		Harrisburg, PA 17105-3608
APVD	J.L.BROSCHARD	5-31-85	NAME	PLUG ASSY, 104 POSN, SIZE 6
PRODUCT SPEC				SERIES 90, BLINDMATE, AMPLIMITE
APPLICATION SPEC			SIZE	CAGE CODE
			A1	00779
MATERIAL	SEE CALLOUTS	FINISH	SEE CALLOUTS	WEIGHT
				SCALE 4:1
				SHEET 1 OF 1
				REV S

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)