



RECOMMENDED PANEL CUTOUT

- CONTACTS TO ACCEPT 14 AWG AND 12 AWG SOLID COPPER WIRE OR 14 AWG STRANDED WIRE WHEN USED WITH AMP 205 SERIES FASTON™ TAB.
- COVER PACKAGED UNASSEMBLED.
- SNAP IN FEATURE ACCOMODATES 0.76-1.78 [.030-.070] PANEL THICKNESS ONLY.
- ALL HOUSINGS AND COVERS ARE UL 94V-2 RATED UNLESS OTHERWISE SPECIFIED.
- UL 94V-0 RATED HOUSING AND COVER.

| | | |
|----------|---------------|--------------|
| OBSOLETE | - | 1-208979-5 |
| | PUTTY WHITE | 1-208979-4 |
| OBSOLETE | BLACK | 5 1-208979-3 |
| | ORANGE | 1-208979-2 |
| | GRAY | 1-208979-1 |
| | GRAY | 1-208979-0 |
| OBSOLETE | CREAM | 208979-9 |
| OBSOLETE | WHITE | 208979-7 |
| | ALMOND | 208979-4 |
| | BLACK | 208979-2 |
| OBSOLETE | BLACK | 208979-1 |
| | HOUSING COLOR | PART NO |

| | | | | |
|--|-----|-------------------------------|------------|--------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN | B.MOYER | 5-1-91 |
| DIMENSIONS: mm[INCHES] | | CHK | R.STONE | 5-7-91 |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD | D.L.ROCKER | 5-7-91 |
| 0 PLC | ± - | NAME | | |
| 1 PLC | ± - | PRODUCT SPEC | | |
| 2 PLC | ± - | APPLICATION SPEC | | |
| 3 PLC | ± - | WEIGHT | | |
| 4 PLC | ± - | SIZE | | |
| ANGLES | ± - | CAGE CODE | | |
| FINISH | - | DRAWING NO | | |
| MATERIAL | | RESTRICTED TO | | |
| HOUSING: NYLON, SEE TABLE | | A2 00779 C-208979 | | |
| COVER: NYLON BLACK | | CUSTOMER DRAWING | | |
| CONTACTS: BRASS | | SCALE 2:1 SHEET 1 OF 1 REV Y1 | | |



RECEPTACLE KIT, UNASSEMBLED, WITH COVER, CONVENIENCE OUTLET

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)