



Identification, colors & marks

Cross section



Components

ID	Quantity	Part number	Description
A	2	1024H0P24	Dielectric
B	1	DRAIN-AWG24-SHCA	24 AWG 19 Strand

Cable

	Description	Thickness		OD	
		Inches	mm	Inches	mm
Outer				0.150	3.81
Core				0.158	4.01
	Wrap	0.004	0.10	0.158	4.01
	Jacket	0.016	0.41	0.190	4.83

Cable OD tolerance + 0.004 + 0.10

Weight 18.21 lb/kt 27.15 Kg/Km

Continued

### Physical properties

Wrap	25% (minimum) overlap
Jacket tensile strength	2000 psi minimum
Jacket elongation	200% minimum

### Electrical properties

Impedance	110 ohms (nominal), Method C, per Raychem Specification 1200
Capacitance - Mutual	TBD pF/ft (nominal) per Raychem Specification 1200
Velocity of Propagation	79% (nominal) per Raychem Specification 1200
Jacket Flaws	Spark Test: 1 kV (rms) Impulse Dielectric Test: 6.0 kV (peak)
Voltage Withstand (dielectric)	1000 volts (rms) conductor to conductor and shield 500 volts (rms) shield to shield when applicable per Spec. 1200

### Notes

Colors	Color code designators shall be in accordance with MIL-STD-681.
Dimensions	Dimensions are in inches, and unless otherwise designated, are nominal.
Identification, Colors & Marks	The following is the key to the descriptions in the left hand view of the cable on Page 1. Line 1: Identifies the component per the components' ID list. Line 2: Color codes. Line 3: Mark on component "-" mark on component jacket.
Minimum length	This cable may be supplied in the following maximum number of continuous lengths : (Order quantity(ft)/300)+1 other length, with no length shorter than 50 ft., unless other specific length requirements are noted.

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)