

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

| LOC | DIST | REVISIONS | | | |
|-----|------|-----------------------|-----------|-----|------|
| P | LTR | DESCRIPTION | DATE | DWN | APVD |
| HC | 00 | REV PER ECO 09-011512 | 5/27/2009 | DW | JO |

NOTES:

- DESIGNED FOR USE WITH .141 SEMI-RIGID (RG402/U) AND CONFORMABLE CABLES WITH SIMILAR DIAMETERS
- ASSEMBLE TO CABLE USING IS 408-8905

16,05
 7,00
 3,20 MAX PANEL
 2,00
 6,46 ACROSS FLAT
 9,5 HEX
 9,5 HEX
 ø5,6

CABLE PREPARATION
SCALE: NTS

2,5
 CABLE INNER CONDUCTOR
 CABLE JACKET

ø7.2 MIN
 6.5 MIN
 RECOMMENDED MOUNTING HOLE
 SCALE: NTS

| | | |
|----------------|------------------|--------|
| CENTER CONTACT | BERYLLIUM COPPER | GOLD |
| HOUSING NUT | BRASS | GOLD |
| WASHER | BRONZE | GOLD |
| DIELECTRIC | PTFE | N/A |
| COMPONENT | MATERIAL | FINISH |

| | | | | |
|-------------|-------------|-----------|-----------|-----------|
| 8-1403077-1 | 5-1403080-9 | 1408411-8 | 1408461-1 | 1408349-1 |
| MTG NUT | WASHER | CONTACT | HSG ASSY | PART NO. |

| | | | | |
|--|-------------|--------------------------|---|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN DCam 11Nov2002 | Tyco Electronics Corporation Norwood, MA 02062 | |
| DIMENSIONS: MM | | CHK - | NAME QMA STRAIGHT CABLE JACK DIRECT SOLDER ATTACHMENT | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD DCam 3/5/04 | RESTRICTED TO | |
| 0 PLC ± - | | PRODUCT SPEC 108-2087 | SIZE A2 | |
| 1 PLC ± - | | APPLICATION SPEC | CAGE CODE 00779 | |
| 2 PLC ± 0,20 | | WEIGHT - | DRAWING NO C=1408349 | |
| 3 PLC ± - | | SCALE 10:1 | | |
| 4 PLC ± - | | SHEET 1 OF 1 | | |
| ANGLES ± 1 | | REV A | | |
| MATERIAL - | FINISH - | CUSTOMER DRAWING | | |

AMP 1471-9 REV 31MAR2000

Downloaded From Onezac.com

1408349

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)