



ELECTRICAL
Nominal Impedance (Ohms) <u>50</u>
Frequency Range (GHz) DC to <u>18.0</u>
Volt Rating (VRMS MAX) @ Sea Level <u>335</u>
VSWR <u>1.05 + .005 f(GHz)</u>
Insertion Loss (dB MAX) <u>.07 √f(GHz)</u>
RF Leakage (dB MIN) <u>-(60-f(GHz))</u>
Corona, 70,000 Ft (VRMS MIN) <u>250</u>
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1000</u>
Contact Resistance (Milliohms MAX) Center Contact <u>3.0</u> Outer Contact <u>2.0</u> Cable to Housing <u>N/A</u>
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>
I.R.(Megohms MIN) <u>5,000</u>

MECHANICAL
Interface Dimensions MIL-STD-348, Fig. <u>310.2</u>
Recommended Mating Torque <u>7-10 IN LBS</u>
Mating Characteristics: Insertion (MAX Lbs) <u>3.0</u> Withdrawal (MIN Oz) <u>1.0</u>
Force to Engage and Disengage (In/Lbs MAX) <u>2.0</u>
Center Contact Captivation Axial (Lbs) <u>6.0</u> Radial (In/Oz) <u>4.0</u>
Cable Retention Axial Force (Lbs) <u>N/A</u> Torque (In/Oz) <u>N/A</u>
Weight (Grams) <u>2.2</u>

ENVIRONMENTAL
Temperature Rating <u>-65°C TO 105°C</u>
Vibration MIL-STD-202, Method 204, Condition D
Shock MIL-STD-202, Method 213, Condition I
Thermal Shock MIL-STD-202, Method 107, Condition A
Moisture Resistance MIL-STD-202, Method 106
Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray

COMPONENT	MATERIAL	FINISH																						
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35																						
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457 AND MIL-P-19468	N/A																						
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B196, ALLOY 173	GOLD PLATE PER MIL-G-45204																						
<table border="1"> <tr> <td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °</td> <td>DRAWN BY P.F. DATE 7/10/79</td> <td colspan="2">AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td> </tr> <tr> <td></td> <td>CHECKED BY R.D.S. DATE 7/11/79</td> <td colspan="2" rowspan="2"> <b>AMP</b>            TITLE            OSM 4 HOLE FLANGE MOUNT            JACK RECEPTACLE TAB TERMINAL         </td> </tr> <tr> <td></td> <td>APPD BY R.M.F. DATE 7/12/79</td> </tr> <tr> <td>USE ASS'Y PROCEDURE</td> <td>NO. AP. <u>N/A</u></td> <td>SIZE B</td> <td>CODE IDENT NO. 26805</td> <td>2052-5636-02</td> <td>REV 05<sub>1</sub></td> </tr> <tr> <td colspan="2"></td> <td>SCALE 5:1</td> <td colspan="3">SHEET 1 OF 1</td> </tr> </table>			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	DRAWN BY P.F. DATE 7/10/79	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599			CHECKED BY R.D.S. DATE 7/11/79	<b>AMP</b> TITLE OSM 4 HOLE FLANGE MOUNT JACK RECEPTACLE TAB TERMINAL			APPD BY R.M.F. DATE 7/12/79	USE ASS'Y PROCEDURE	NO. AP. <u>N/A</u>	SIZE B	CODE IDENT NO. 26805	2052-5636-02	REV 05 <sub>1</sub>			SCALE 5:1	SHEET 1 OF 1		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	DRAWN BY P.F. DATE 7/10/79	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																						
	CHECKED BY R.D.S. DATE 7/11/79	<b>AMP</b> TITLE OSM 4 HOLE FLANGE MOUNT JACK RECEPTACLE TAB TERMINAL																						
	APPD BY R.M.F. DATE 7/12/79																							
USE ASS'Y PROCEDURE	NO. AP. <u>N/A</u>	SIZE B	CODE IDENT NO. 26805	2052-5636-02	REV 05 <sub>1</sub>																			
		SCALE 5:1	SHEET 1 OF 1																					

CUSTOMER DRAWING AMP PART # 1052898-1 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)