



RECOMMENDED PC BOARD MOUNTING DIMENSIONS
FOR 1.60[.063] THICK PC BOARD AND
0.305[.012] STENCIL THICK

- 1 TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
- 2 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- 3 RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
- 4 $\oplus 0.51 [0.020] M$ FOR KINKED TAILS.
- 5 HOUSING: LCP, COLOR-BLACK.
POST: PHOSPHOR BRONZE.
- 6 0.000076[.000003] MIN GOLD OVER 0.00068[.000027] Pd/Ni IN CONTACT AREA.
0.00254-0.00508 [.000100-.0000200] MATTE TIN ON SOLDER TAIL,
ALL OVER 0.00127 [.000050] NICKEL.

6	101.19 [3.984]	99.06 [3.900]	39	80	8-1977952-0
6	2.13 [.084]	-	-	2	1977952-2
FINISH	C	B	A	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN KIRAN HOLAL 31AUG2013	CHK MIKE MILLER 31AUG2013	NAME MIKE MILLER 31AUG2013	TE Connectivity
0 PLC ± -	1 PLC ± -	2 PLC ± 0.51[.02]	3 PLC ± 0.12[.005]	4 PLC ± 0.012[.0005]	ANGLES ± -
MATERIAL	FINISH SEE TABLE	WEIGHT	SIZE A1	CAGE CODE 00779	DRAWING NO 1977952
CUSTOMER DRAWING		SCALE	4:1	SHEET	1 OF 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)