

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT copyright\_date BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A2	REDRAWN TO CREO	19APR2017	JJH	JP

1. DELIVERY STATE: WRAPPED UP ROLL WITH STEP BETWEEN TERMINALS =  $11.9 \pm 0.2$ mm  
 STATO DI FORNITURA: AVVOLTI SU BOBINA CON PASSO TRA TERMINALI DI =  $11.9 \pm 0.2$ mm

2. SUITABLE FOR SINGLE WIRE SEAL TE PN 281934  
 ADDETTO PER GOMMINO TE 281934

3. MAX. CURRENT CAPACITY: 14A

CUSTOMER DRAWING FOR INFORMATION ONLY  
 DISEGNO PER CLIENTE SOLO PER RIFERIMENTO

PRE-TIN  
 (PRE-STAGNATO)

BRASS  
 (OTTONE)

282465-1

FINISH/COLOUR  
 (FINITURE/COLORE)

MATERIAL  
 (MATERIALE)

PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN BERTINI 12DEC1992

CHK A. BRUNI 12DEC1992

APVD -

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

NAME  
 MINI MIC RS TAB CONTACT

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

-

©=282465

SCALE 5:1

SHEET 1 OF 1

REV A2

DIRECTION OFF TOP OF REEL

"U"-SIDE UP

INS. DIA. RANGE  
 (DIAM. ISOLANTE)

WIRE RANGE  
 (RANGO FILO)

2

1.5-2.5mm<sup>2</sup>

DIMENSIONS:

mm

TOLERANCES UNLESS  
 OTHERWISE SPECIFIED:

±0.3

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±2°

FINISH

-

MATERIAL

-

1470-19 (3/13)

Downloaded From [Oneyac.com](http://Oneyac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)