

4 3 2 1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - TE CONNECTIVITY ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
CM	54	P	LT	DESCRIPTION	DATE	DM	APD
		W		REVISED PER ECR-20-000820	27MAY2020	PC	SW

95.10	[3.744]	24	5-640605-4
91.14	[3.588]	23	5-640605-3
87.17	[3.432]	22	5-640605-2
83.21	[3.276]	21	5-640605-1
79.25	[3.120]	20	5-640605-0
75.29	[2.964]	19	4-640605-9
71.32	[2.808]	18	4-640605-8
67.36	[2.652]	17	4-640605-7
63.40	[2.496]	16	4-640605-6
59.44	[2.340]	15	4-640605-5
55.47	[2.184]	14	4-640605-4
51.51	[2.028]	13	4-640605-3
47.55	[1.872]	12	4-640605-2
43.59	[1.716]	11	4-640605-1
39.62	[1.560]	10	4-640605-0
35.66	[1.404]	9	3-640605-9
31.70	[1.248]	8	3-640605-8
27.74	[1.092]	7	3-640605-7
23.77	[.936]	6	3-640605-6
19.81	[.780]	5	3-640605-5
15.85	[.624]	4	3-640605-4
11.89	[.468]	3	3-640605-3
7.92	[.312]	2	3-640605-2

	DIM A	NO OF CIRCUITS	PART NO
SUPERSEDED	95.10 [3.744]	24	2-640605-4
SUPERSEDED	91.14 [3.588]	23	2-640605-3
SUPERSEDED	87.17 [3.432]	22	2-640605-2
SUPERSEDED	83.21 [3.276]	21	2-640605-1
SUPERSEDED	79.25 [3.120]	20	2-640605-0
SUPERSEDED	75.29 [2.964]	19	1-640605-9
SUPERSEDED	71.32 [2.808]	18	1-640605-8
SUPERSEDED	67.36 [2.652]	17	1-640605-7
SUPERSEDED	63.40 [2.496]	16	1-640605-6
SUPERSEDED	59.44 [2.340]	15	1-640605-5
SUPERSEDED	55.47 [2.184]	14	1-640605-4
SUPERSEDED	51.51 [2.028]	13	1-640605-3
SUPERSEDED	47.55 [1.872]	12	1-640605-2
SUPERSEDED	43.59 [1.716]	11	1-640605-1
SUPERSEDED	39.62 [1.560]	10	1-640605-0
SUPERSEDED	35.66 [1.404]	9	640605-9
SUPERSEDED	31.70 [1.248]	8	640605-8
SUPERSEDED	27.74 [1.092]	7	640605-7
SUPERSEDED	23.77 [.936]	6	640605-6
SUPERSEDED	19.81 [.780]	5	640605-5
OBSOLETE	15.85 [.624]	4	640605-4
SUPERSEDED	11.89 [.468]	3	640605-3
SUPERSEDED	7.92 [.312]	2	640605-2

1 MATERIAL: CONNECTOR - NYLON UL94V-2 (YELLOW).
 CONTACTS - 0.30[.012] THICK COPPER ALLOY
 (BRIGHT TIN-LEAD 0.00203[.000080] MIN. THICK
 FOR CONTACTS 640605-2 THRU 2-640605-4)
 (MATTE WHISKER MITIGATED TIN 0.00203[.000080] MIN
 THICKNESS OVER NICKEL UNDERPLATE FOR
 3-640605-2 THRU 5-640605-4).

2 CONTACTS ACCEPT 20 AWG WIRE WITH 2.41[.095] MAX INSULATION DIAMETER.

3 CONTACTS MUST ACCEPT 1.14±0.03[.045±.001] SQUARE POST AND REMAIN LOCKED IN POSITION.

4 IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY NOT APPEAR ON ALL ASSEMBLIES.

5 DIMENSIONS IN BRACKETS ARE IN INCHES.

6 HOUSING FEATURES ARE: FEED-THRU WITHOUT LOCKING RAMP.

7 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

8 OBSOLETE PARTS

THIS DRAWING IS A CONTROLLED DOCUMENT.

DM: B. LEWIS 12FEB91
 CHK: R. SWING 12FEB91
 APD: D. CLARK 19FEB91

TE Connectivity
 MTA-156 CONNECTOR ASSEMBLY,
 20 AWG, STANDARD

PRODUCT SPEC: 108-1051
 APPLICATION SPEC: 114-1020

SIZE: A2 CAGE CODE: 00779 DRAWING NO: 640605
 WEIGHT: RESTRICTED TO: -

CUSTOMER DRAWING SCALE: 4:1 SHEET: 1 of 1 REV: W

1471-9 (3/11)

Downloaded From Oneyac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)