

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
D		REVISED PER ECO-17-002903	20MAR2017	AP DG

1	RCPT ACCEPTS SIZE 20 DF SOCKET CONTACTS. CONTACTS MUST BE PURCHASED SEPARATELY.	6	CARBON STEEL, C1022.
2	ALL PARTS SHIPPED UNASSEMBLED.	7	.000200 MIN TIN PLATE OVER .000100 MIN COPPER UNDERPLATE.
3	FLAME RETARDANT 94V-0 RATED, STYRENE POLYOLEFIN OR PVC, BLACK.	8	BLACK ZINC FLAKE COATING.
4	FLAME RETARDANT 94V-0 RATED GLASS FILLED, NYLON OR POLYESTER, BLACK.	9	COMPONENTS INDIVIDUALLY BULK PACKED.
5	STEEL PER ASTM A109.		

FERRULE (MUST BE PURCHASED SEPARATELY AS REQD BY CABLE DIA)

EXPANDING NECK ACCOMMODATES CABLE FROM .338-.562 DIA

.125 MAX

#4-40 JACKSCREW QTY:2

5 7 SHIELD QTY:2

3 ENCLOSURE

.812 TYP

1.467 TYP

2.775 MAX

1 4 5 7 HDP-20 RCPT CONNECTOR

.730 MAX

CABLE REF

2.010 MAX

2.406 ±.005

9	W/ LOGOS	5747959-1
PACKAGING	REMARKS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN G. ATTADIA - DOCK5 11-10-04	STE TE Connectivity	
DIMENSIONS: INCHES		CHK J. GERACE 11-10-04		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. WALMSLEY 11-10-04	NAME	
0 PLC ± -		PRODUCT SPEC	BULK KIT, RCPT, AMPLIMITE SHIELDING ENCLOSURE, 50 POSN, SIZE 5, HDP-20	
1 PLC ± -		APPLICATION SPEC	SIZE	CAGE CODE
2 PLC ± -		114-40030	A2	00779
3 PLC ± .020		WEIGHT	C=5747959	
4 PLC ± -		0.000000	SCALE	SHEET
ANGLES ± -		CUSTOMER DRAWING	2:1	1 of 1
FINISH			REV	D
3 4 5 6	7 8			

1471-9 (1/15) Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)

[>>点击查看相关商品](#)