

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	12NOV2014	DW	CW
	B	ECR-20-016101	09JUN2021	BS	CW

M4 SCREW  
RECOMMENDED  
TIGHTENING TORQUE 1.2Nm

4X M3 SCREW, RECOMMENDED  
TIGHTENING TORQUE 0.5Nm

PANEL CUT FOR INSERTS FOR USE  
WITHOUT HOODS/ HOUSINGS

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 250 V  
RATED CURRENT: 16 A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 4 KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE: 0.14-4 mm<sup>2</sup> (26-12 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20300X10XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 250V  
额定电流: 16A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 4 KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
接线范围: 0.14-4 mm<sup>2</sup> (26-12 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20300X10XX000)

HA-016-MC	T2010164101-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	12NOV2014	 TE Connectivity	NAME	HA-016-MC	
DIMENSIONS:		CHK	12NOV2014				
mm		APVD	12NOV2014				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	108-137045				
0 PLC ±-		APPLICATION SPEC	114-137045	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
1 PLC ±-		WEIGHT	-	A3	00779	©-T2010164101000	-
2 PLC ±-		Customer Drawing		SCALE	1:1	SHEET	1 OF 1
3 PLC ±-				REV	B		
4 PLC ±-							
ANGLES ±-							
FINISH							
-							
-							

1470-19 (3/13)

Downloaded From [Oneyac.com](http://Oneyac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)