



P.C. BOARD MOUNTING DIMENSIONS

- △ HOUSING: SPS, UL 94V-0 RATED, BLACK.
- △ CONTACT: BRASS.
- △ .076um MINIMUM GOLD OVER 0.76um MINIMUM PALLADIUM NICKEL ON MATING AREA, 3.80um MINIMUM TIN ON SOLDER TAIL, ALL OVER 1.27um MINIMUM NICKEL.
- △ DATUMS AND DIMENSIONS ESTABLISHED BY CUSTOMER.
- △ RECOMMENDED MINIMUM TRACE WIDTH FOR END POSITIONS WHEN CARRYING 3 AMPS: 1.8 WIDE x 55um THICK, BOTH SIDES.

5787531-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE: 07-08-99	BY: R.S.KLINE	REVISED: 07-11-99	BY: R.S.KLINE	DATE: 07-11-99	BY: R.S.KLINE	DATE: 07-11-99	BY: R.S.KLINE	DATE: 07-11-99	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		APPLICATION SPEC		MATERIAL		FINISH	
0 PLC	± .01	1 PLC	± .013	2 PLC	± .013	3 PLC	± .013	4 PLC	± .013	5 PLC	± .013
MATERIAL: △ △		FINISH: △		WEIGHT: -		SCALE: A1		DATE CODE: 00779		DRAWING NO: 5787531	
CUSTOMER DRAWING		RESTRICTED TO: -		SHEET: 1		OF: 1		REV: 0		SCALE: 8:1	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)