


<b>SPECIFICATION CONTROL DRAWING</b>		<b>82A1822</b>	
Title	TWO CONDUCTOR CABLE, SHIELDED, JACKETED, GENERAL PURPOSE, FLEXIBLE, 600 VOLT	Date:	2-15-07
		Revision:	A
This specification sheet forms a part of the latest issue of Raychem Specification 80.			



CABLE CONSTRUCTION DETAILS							
PART NUMBER 1/	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (in.)		OUTSIDE DIAMETER (in.)		MAXIMUM WEIGHT (lbs/1000 ft.)
			MINIMUM	NOMINAL	NOMINAL	MAXIMUM	
82A1822-26-*	26	38	.007	.009	.111	.117	9.8
82A1822-24-*	24	38	.007	.010	.125	.131	12.6
82A1822-22-*	22	38	.007	.011	.147	.154	17.0
82A1822-20-*	20	38	.008	.012	.169	.177	22.0
82A1822-18-*	18	38	.009	.013	.195	.205	30.2
82A1822-16-*	16	38	.009	.014	.229	.240	41.4

CABLE RATINGS AND ADDITIONAL REQUIREMENTS


TEMPERATURE RATING: 150°C  
Maximum continuous conductor temperature  
VOLTAGE RATING: 600 volts (rms) at sea level  
CROSSLINKING PROOF TEST: 300 ± 3°C for 1 hour  
DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz  
JACKET COLOR: White preferred  
JACKET ELONGATION AND TENSILE STRENGTH:  
Elongation, 100% (minimum)  
Tensile Strength, 3000 lbf/in<sup>2</sup> (minimum)  
JACKET FLAWS:  
Spark Test, 1500 volts (rms)  
Impulse Dielectric Test, 6.0 kV (peak)

SECANT MODULUS (Test per ASTM D 882):  
4.0 x 10<sup>4</sup> lbf/in<sup>2</sup> (minimum),  
2% strain, 2 inch jaw separation, 0.2 inch/minute  
SHIELD COVERAGE: 85% (minimum)  
VOLTAGE WITHSTAND (Post Environmental)  
1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:  
The "\*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.

1/ Example: AWG 22, black and brown component wires;  
white jacket: 82A1822-22-0/1-9

NOTE: Nominal values are for information only.  
Nominal values are not requirements.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.			
Page 1 of 1	DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL		 <b>Raychem</b> Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.		

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)