



ALTERNATE SECTION A-A

NOTES:

- 1. ACCEPTS TERMINALS 60949, 60950, 60951, 60994, 60995, 60996
- 2. MATES WITH 480373
- △ A .105 DIA PIN MUST ENTER CAVITY WITH A MAX FORCE OF 5 OUNCES
- △ .005 MAX FLASH PERMITTED
- △ OPTIONAL FEATURE - SEE ALTERNATE SECTION A-A.
- △ OPTIONAL CONFIGURATION - SEE ALTERNATE SECTION A-A.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△ .110/.105 DIA
 ⊕ C D .007

Unpublished copy not to be reproduced nor published without written permission of AMP Incorporated.

REV	DESCRIPTION	BY	CHK	DATE
G1	ECO-09-025699	KK	HMR	JAN10
G	REV PER CM-1015	PKC	TB	10-14-82
F	RESTORATION	KS	ST	5-6-85
E	REV, M-7432	ST	ST	11-9-82
D	REV	AK	ST	1-15-82
C	REV	AK	ST	1-15-82
B	REV	AK	ST	1-15-82
A	REV	AK	ST	1-15-82

QTY	DESCRIPTION	REMARKS

DWG SIZE	NUMBER	NAME	REMARKS	ITEM NO
© 1966 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.			CUSTOMER COPY REFERENCE ONLY	
DR	6-6-72	MATERIAL AND FINISH	AMP INCORPORATED HARRISBURG, PENNA.	
CHK	6-12-72	SEE CHART	CLASS .026 SOCKET HOUSING	
DE	6-12-72	WIRE - RANGE - INSULATION	TYPE #	
APP		TOLERANCE EXCEPT AS NOTED ±.015	SCALE 2X1	NO 480374
NAME			REV G1	
B CIRCUIT DUAL-IN-LINE PLUG				

07AB-14-59-AD

1-480374-0	NYLON	NATURAL
△ 1-480374-1	NYLON	BLACK
PART NUMBER	MATER	Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)