



| REVISIONS | | | |
|-----------------|-------------|---------------|----------------------|
| REV | DESCRIPTION | DATE | APPROVED |
| 01 ₃ | REVISED | DM 9/13/99 | <i>DM</i> 9/20/99 |

| | | |
|-------------------------|--|-------------------------------|
| HOUSING COUPLING NUT | STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 | PASSIVATE PER ASTM-A380 |
| DIELECTRIC | TFE FLUOROCARBON PER ASTM-D-1457 | N/A |
| CENTER CONTACT | BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H | GOLD PLATE PER MIL-G-45204 |
| RETAINING RING | BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H | N/A |
| GASKET | SILICONE RUBBER PER ZZ-R-765 | N/A |

| COMPONENT | MATERIAL | FINISH |
|-----------|----------|--------|
|-----------|----------|--------|

| | | | |
|---|--------------------------|-----------------------|--|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1° | DRAWN BY RBG | DATE 6/4/77 | AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 |
| | CHECKED BY KWW | 6/4/77 | |
| | APPRD BY RMF | 6/4/77 | |

- NOTES:
- CAPTURED CENTER CONTACT
 - VSWR: DC-12.4GHz :1.06+.005fGHz MAX
12.4-18.0GHz : 0.83+.023fGHz MAX

| | | | | |
|---|--------------------|---|-------------------------|------------------------|
| These drawings and specifications are the property of AMP Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission. | USE ASSY PROCEDURE | TITLE TYPE N PLUG TO SMA JACK ADAPTER | | |
| | NO. A.P. _____ | SIZE B | CODE IDENT NO. 26805 | 3082-2240-00 |
| | | SCALE 5:1 | | REV 01 ₃ |

CUSTOMER DRAWING

AMP PART # 1057377-1
SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)