



- ⚠ MATERIAL:
 - HERMAPHRODITIC BACKSHELL- STEEL.
 - SPRING LATCH- STAINLESS STEEL.
 - HERMAPHRODITIC SPRING LATCH COVER- UL 94V-0 RATED ABS MOLDING COMPOUND, COLOR-BLACK.
- ⚠ PLATING:
 - HERMAPHRODITIC BACKSHELL- 5µm MIN BRIGHT NICKEL OVER 2.5µm MIN COPPER.
- ⚠ RECOMMENDED WIRE: 30 AWG WITH A 0.56-0.64 INSULATION DIAMETER, WIRE MUST BE APPROVED BY AMP ENGINEERING.

INDIVIDUAL KIT	787133-2
BULK KIT	787133-1
PACKAGING TYPE	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009		DIN T. SHUEY CHK J. GERACE APD M. WALMSLEY NAME DEBAROS		STE TE Connectivity	
DIMENSIONS: mm 0. PLC ± - 1. PLC ± - 2. PLC ± 0.13 3. PLC ± - 4. PLC ± - ANGLES ± -		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0. PLC ± - 1. PLC ± - 2. PLC ± 0.13 3. PLC ± - 4. PLC ± - ANGLES ± -		PRODUCT SPEC 108-1471 APPLICATION SPEC	
MATERIAL		FINISH		SIZE CASE CODE DRAWING NO A1 00779 C=787133	
CUSTOMER DRAWING		SCALE 5:1		SHEET 1 OF 1 REV E	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)