



DESIGNED FOR USE WITH	.141 S.R.
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.143
CONTACT	.037

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
010	RELEASED	10/14/96	[Signature]

COMPONENT	MATERIAL	FINISH
HOUSING EXTRA HOUSING CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204
COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. 310-1	Temperature Rating <u>-65°C to 165°C</u>
Frequency Range (GHz) DC to <u>12.4</u>	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D
Volt Rating (VRMS MAX)	Torque <u>7 to 10 In-Lbs</u>	Shock MIL-STD-202, Method 213, Condition I
@ Sea Level <u>500</u>	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B,
VSWR <u>1.10 +0.01 f(GHz)</u>	Insertion (MAX Lbs) <u>N/A</u>	Except High Temp <u>+115°C</u>
Insertion Loss (dB MAX) <u>.05 x√ f(GHz)</u>	Withdrawal (MIN Oz) <u>N/A</u>	Moisture Resistance MIL-STD-202, Method 106
RF Leakage (dB MIN) <u>-90 @ 2 to 3 GHz</u>	Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) <u>375</u>	Center Contact Captivation	
Dielectric Withstanding Voltage	Axial (Lbs) <u>6.0</u>	
(VRMS MIN) @ Sea Level <u>1,500</u>	Radial (In-Oz) <u>4.0</u>	
Contact Resistance (Milliohms MAX)	Cable Retention	
Center Contact <u>4.0</u>	Axial Force (LXs) <u>60</u>	
Outer Contact <u>2.0</u>	Torque (In-Oz) <u>55</u>	
Cable to Housing <u>0.5</u>	Weight (Grams) <u>TBD</u>	
RF High Potential @ Sea Level		
(VRMS MIN @ 5 MHz) <u>1,000</u>		
IR.(Megohms MIN) <u>5,000</u>		

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES

FRAC. ± 1/64	DEC. ±.005	ANGLES ± 1°
-----------------	---------------	----------------

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

USE ASS'Y PROCEDURE

NO. AP. 408-04916 (20-548)

DRAWN BY [Signature] DATE 9/3/96

CHECKED BY [Signature]

APPD BY [Signature] DATE 10/14/96

AMP Incorporated  
140 Fourth Avenue  
Waltham, MA 02451-7599

TITLE "OSM" RIGHT ANGLE CABLE PLUG  
DIRECT SOLDER ATTACHMENT  
M39012/80B3002 CAT B

SIZE B	CODE IDENT NO. 26805	2007-8002-92	REV 010
-----------	-------------------------	--------------	------------

SCALE 5:1 SHEET 1 OF 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)