

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AF	50	P	LTR	DESCRIPTION	DATE	DWN	APVD
		D		REVISED PER ECR-13-011489	14DEC2013	KH	PD

SUGGESTED MATING TAB

Technical drawing of a suggested mating tab. Key dimensions include: 1.02 [.040] / 0.76 [.030] (width), 3.38 [.133] / 2.97 [.117] (width with callout 4), 1.52 [.060] / 1.27 [.050] (width), 5.40 [.213] MIN (height), 4.83 [.190] / 4.67 [.184] (height), 3.30 [.130] / 3.10 [.122] (width), 1.14 [.045] / 0.89 [.035] X 45° (width), 6.35 [.250] (width), 8.26 [.325] (width), 0.25 [.010] (width), 0.53 [.021] / 0.48 [.019] (width), 0.13 [.005] R MAX BOTH SIDES (radius), and 10° ±2° (angle).

- MATL: #2 HARD BRASS OR NICKEL PLATE STEEL.
- NO BURRS PERMISSIBLE AT HOLE.
- TIN PLATING IS REQUIRED ON BRASS WHEN TERMINAL TEMPERATURE IS OVER 225° F.
- MUST BE FLAT WITHIN 0.076 [.003] OVER THIS LENGTH.
- HOLE MUST BE SYMMETRICAL ABOUT TAB & WITHIN 0.076 [.003].

* TO BE USED ONLY WHEN SHOULDER IS ELIMINATED.

SECTION A-A: Cross-section of the receptacle. Dimensions include: 17.02 [.670] (total length), 3.43 [.135] (width), and 6.30 [.248] (width).

SECTION C-C: Cross-section of the receptacle. Dimensions include: 6.48 [.255] (width), 3.56 [.140] (width), 1.91 [.075] (width), and 0.356 ± 0.025 [.014 ± 0.001] (width).

SECTION A-A

SECTION C-C: Cross-section of the receptacle. Dimensions include: 4.57 [0.180] / 3.94 [0.155] (width), and 3.78 [.149] REF (width).

SECTION C-C

SECTION B-B ROTATED 90° CW: Cross-section of the receptacle. Dimensions include: 5.94 [.234] (width), 1.65 [.065] (width), and 2.59 [.102] (width).

SECTION B-B
ROTATED 90° CW

SECTION D-D: Cross-section of the receptacle. Dimensions include: 6.98 [0.275] / 6.35 [0.250] (width), and 5.84 [.230] REF (width).

SECTION D-D

- CONTINUOUS STRIP ON REELS.
- ACCEPTS [#18-#14] SINGLE WIRE SIZES AND COMBINATION OF TWO [#18'S]. WIRE CRIMP IS 3.05 [.120], F TYPE.
- FITS INSULATION RANGE OF 3.81-5.08 [.150-.200] DIA OR TWO WIRES AT 2.79 [.110] MAX DIA. INSULATION CRIMP IS 5.59 [.220], F TYPE.

0.002032 [.000080] MIN TIN	1217114-2
-	1217114-1
FINISH	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	JR RUTH	9/17/98
DIMENSIONS:		CHK	MS FEHER	9/17/98
mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD	E HOWARD	9/17/98
	0 PLC ± -	PRODUCT SPEC		
	1 PLC ± -	APPLICATION SPEC		
	2 PLC ± 0.25 [.010]			
	3 PLC ± -			
	4 PLC ± -			
	ANGLES ± -			
MATERIAL	FINISH	WEIGHT		
BRASS	SEE TABLE			
CUSTOMER DRAWING		SCALE	6:1	SHEET
		SIZE	A2	00779
		DRAWING NO	C=1217114	
		RESTRICTED TO	-	

1471-9 (3/11)

Downloaded From Onevac.com

1217114

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)