

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
AB2		REVISED PER ECO-14-008433	05JUN2014	NK MZ
AC		REVISED PER ECO-17-000037	10MAR2017	RS MZ

.9375-20 UNEF-2B THREAD

SLEEVE

TUBING

A±.25

1.00 MIN

.975 MIN

.060±.015

TE 54011-5

MARKING DETAIL

1 POLYOLEFIN, BLACK.

2 NYLON, BLACK.

3 NOMINAL WALL THICKNESS, EXPANDED.

4 LENGTH OF SEALANT.

5 EXPANDED INSIDE DIAMETER.

6 9.52[.375] MAXIMUM RECOVERED INSIDE DIAMETER.

7 ASSEMBLY WILL PASS 0.0703 KG PER SQ CENTIMETER [ONE POUND PER SQ IN.] WATER PRESSURE TEST.

8 121°C [250°F] SHRINK TEMPERATURE.

9 -55°C TO 110°C [-67°F TO 230°F] OPERATING TEMPERATURE.

10 THIS PART WILL ACCOMMODATE  $\phi 10.16 - \phi 22.22$  [ $\phi 400 - \phi .875$ ] CABLE RANGE.

11 ACTUAL SHAPE MAY VARY DUE TO PROCESS VARIANCE.

12 SEE P/N CHART FOR MARKING. WHITE CHARACTERS .150 MIN HIGH AND LOCATED ON THE OUTSIDE SURFACE OF THE TUBING.

13 OBSOLETE PART.

TE 54011-5	2.50	13 54011-5
NONE	4.00	54011-4
NONE	3.25	54011-3
NONE	2.50	54011-1
MARKING	A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.REIFSNYDER 10 APR 96	TE Connectivity	
DIMENSIONS: INCHES		CHK R.STONE 15 APR 95	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD T.A.WETZEL 03 MAY 96	STRAIN RELIEF ASSY, SHELL SIZE 17, CPC	
0 PLC ± -		PRODUCT SPEC	SIZE	RESTRICTED TO
1 PLC ± -		APPLICATION SPEC	CAGE CODE	
2 PLC ± -		WEIGHT	DRAWING NO	
3 PLC ± -		FINISH	SCALE	
4 PLC ± -			SHEET	
ANGLES ± -			REV	
MATERIAL TUBING: 1 SLEEVE: 2		CUSTOMER DRAWING	A2 00779 C=54011	AC

1471-9 (1/15)

Downloaded From [Onevac.com](http://Onevac.com)

54011

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)