



DESIGNED FOR USE WITH RG-196/U	
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.037
CONTACT	.012
FERRULE	.098

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₂	REVISED	K.L. 7-26-96 8/7/96	<i>[Signature]</i>
B	PER EC 0U20-0116-01-02	10/29/01	C. Hoang

COMPONENT	MATERIAL	FINISH
HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		DRAWN BY DJC 2-22-68		DATE 2-22-68		AMP Incorporated	
FRAC. ± 1/64	DEC. ±.005	ANGLES ± 1°	CHECKED BY PRB 2-22-68		140 Fourth Avenue Waltham, MA 02451-7599		
These drawings and speci- fications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale o f item(s) without written permission.			APPD BY PRB 2-22-68		TITLE "OSMM" STRAIGHT CABLE PLUG CRIMP ATTACHMENT		
.XXX = in XX.X = mm (REF)			USE ASSY PROCEDURE		NO. A.P.	40-001	408-08250
SCALE 8:1		SIZE B	CODE IDENT NO. 26805	4031-7196-00	REV 02 ₂	SHEET 1 OF 1	

CUSTOMER DRAWING

AMP PART # 1059057-1
SHEET 1 OF 1 REV B

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)