SPECIFICATION CONTROL DRAWING

CHEMINAX

.0200

.049

.070

.090

(nominal)

.103

(maximum)

 $\pm .003$

41 OHM, AWG 26, 19 STRANDS OF AWG 38, COAXIAL CABLE

Date: С Revision:

4126C1332

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

CONSTRUCTION DETAILS

ELECTRICAL CHARACTERISTICS

DIMENSIONS ARE NOMINAL VALUES IN INCHES, UNLESS OTHERWISE DESIGNATED.

CHARACTERISTIC IMPEDANCE 41 ± 2 ohms, Method A **CAPACITANCE** 35.3 pF/ft. (minimum), 42.0 pF/ft. (maximum)

VELOCITY OF PROPAGATION

64% (nominal)

CONDUCTOR AWG 26.

DIELECTRIC

Rayolin F

SHIELD

JACKET

Thermorad S

AWG 36.

Color - Natural

19 Strands of AWG 38, Silver-Coated Copper

Silver-Coated Copper

ELECTRICAL

CONDUCTOR RESISTANCE 36.4 ohms/1000 ft. (nominal)

INSULATION RESISTANCE 10,000 megohms (minimum) for 1000 ft.

ADDITIONAL REQUIREMENTS

JACKET FLAWS

SPARK TEST 1.0 kV (rms) IMPULSE TEST 6.0 kV (peak) **VOLTAGE WITHSTAND** 1500 volts (rms)

(DIELECTRIC)

ENVIRONMENTAL

FLAMMABILITY Method C **HEAT SHOCK** 225°C

LOW TEMPERATURE-COLD BEND -55°C/2.50 inch mandrel **VOLTAGE WITHSTAND** 1000 volts (rms), 1 minute (Post Environmental)

PHYSICAL

INSULATION (DIELECTRIC)

ELONGATION 200% (minimum) TENSILE STRENGTH 1800 lbf/in2 (minimum)

JACKET

ELONGATION 200% (minimum) 2000 lbf/in2 (minimum) TENSILE STRENGTH JACKET THICKNESS .010 inch (nominal) SHIELD COVERAGE 90% (minimum)

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Unless otherwise specified, outer jacket color will be black designated by a "-0" appended to the part number, (e.g. 4126C1332-0).

Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

WEIGHT

TEMPERATURE RATING

ENGINEERING REFERENCE

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

Rayolin, Thermorad, Cheminax, Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.



Raychem Wire & Cable 501 Oakside Avenue Redwood City, California 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297 THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

© 2007-2015 Tyco Electronics Corporation. All rights reserved.

7.3 lbs/1000 ft. (nominal)

110°C (maximum)

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)