



- THIS PLUG WILL MATE WITH ANY 44 POSN., SIZE 3 RECEPTACLE IN AMPLIMITE SERIES.
- MAXIMUM WIRE INSULATION TO BE USED WITH THIS PLUG IS .054 DIA.
- SST RETENTION CLIPS ARE INCLUDED IN INSERTS.
- THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308.
- CONNECTOR SUPPLIED WITHOUT CONTACTS; SHOWN FOR ILLUSTRATION ONLY.
- THIS PLUG WILL ACCEPT SIZE 22 DM PIN CONTACT M39029/58-22-22D OR ANY AMP SIZE 22 DF PIN CONTACT.

- UL/CSA DESIGNATION STAMPED IN THIS AREA.
- 8 100% INSPECTION REQUIRED.
 - 9 THIS FEATURE TO BE MEASURED WHILE COMPRESSED.
 - 10 FINISH: CADMIUM PER QQ-P-416; YELLOW CHROMATE.
 - 11 FINISH: ZINC PLATED PER ASTM-B-633 .000200 MIN THK WITH SUPPLEMENTARY CHROMATE (Cr3+).

8	9	11	5-445011-2
--	--	11	5-445011-1
8	9	10	445011-2
--	--	10	445011-1
REMARKS	FINISH	PART NO.	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN S. GLATFELTER 10-17-85	DM
0 PLC ± -	1 PLC ± -	CHK F. C. BALLEW 10-17-85	BY
2 PLC ± -	3 PLC ± .005	APP'D F. BALLEW 10-17-85	DATE
4 PLC ± -	ANGLES ± -	NAME	RESTRICTED TO
MATERIAL SEE CALLOUT	FINISH SEE CALLOUT	WEIGHT	SIZE CASE CODE DRAWING NO
			A1 00779 C=445011
		CUSTOMER DRAWING	SCALE 4:1 SHEET 1 OF 1 REV R

tyco Electronics Tyco Electronics Corporation Harrisburg, PA 17105-3608

PLUG ASSY, AMPLIMITE, 44 POSN., SIZE 3, SERIES 90, BLINDMATE

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)