



- △ COUPLING RING: POLYPHENYLENE, BLACK.
ADAPTER, HOUSING AND PRESSURE PLATE: NYLON, BLACK.
WIRE ENTRY SEAL: ELASTOMER, RED-IRON OXIDE.
- 2. CONNECTOR WILL ACCEPT (37) MULTIMATE SOCKET CONTACTS.
- △ 3. ORIENTATION HOLE USED IN THE MANUFACTURING PROCESS ONLY.
THIS HOLE IS NOT INTENDED FOR WIRE INSERTION.

796288-1
PART NUMBER

| | | | | | |
|--|--|--|--|--|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DIN C. DORWART 11 NOV 98 | | TE Connectivity | |
| DIMENSIONS: INCHES | | TOLERANCES UNLESS OTHERWISE SPECIFIED: | | | |
| 0 PLC ± - 1 PLC ± - 2 PLC ± 0.13(.005) 3 PLC ± - 4 PLC ± - ANGLES ± - | | CJK K. DOWHOWER 15NOV99 APVD K. DOWHOWER 15NOV99 NAME: PLUG ASSEMBLY, SIZE 23-37, STANDARD SEX, SERIES I, SEALED CIRCULAR PLASTIC CONNECTOR PRODUCT SPEC: 108-1579 APPLICATION SPEC: | | SIZE: A1 CAGE CODE: 00779 DRAWING NO: 796288 RESTRICTED TO: | |
| MATERIAL: △ 1 | | FINISH: - | | WEIGHT: - CUSTOMER DRAWING: | |
| | | SCALE: 2:1 | | SHEET 1 OF 1 REV C | |

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)