



SECTION A - A

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASED	20SEP2023	DW	CW

NOTES:

- TECHNICAL CHARACTERISTICS:
 CONTACT MATERIAL: COPPER ALLOY
 SURFACE PLATING: SILVER
 CONTACT RESISTANCE: $\leq 3.0\text{m}\Omega$
 WIRE RANGE: 4.0-6.0 mm² (12-10 AWG)

注释:

- 技术参数:
 公针材料: 铜合金
 表面电镀: 镀银
 接触电阻: $\leq 3.0\text{m}\Omega$
 接线范围: 4.0-6.0 mm² (12-10 AWG)

PART NUMBER 料号	PART DESCRIPTION 描述	Ød	ØD	WIRE GAUGE 线规		STRIPPING LENGTH 剥线长度 (mm)
				MM ²	AWG	
T2040051040-001	HMM-4.0 HMM公针 4.0mm ² , 镀银, 高插拔, L=35	2.85	3.85	4.0	12	9.2
T2040051060-001	HMM-6.0 HMM公针 6.0mm ² , 镀银, 高插拔, L=35	3.50	5.00	6.0	10	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	DAVID WANG	21SEP2023
CHK	GINO YAO	21SEP2023
APVD	CHRIS WANG	21SEP2023

STE TE Connectivity

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
mm		0 PLC	±
		1 PLC	±
		2 PLC	±
		3 PLC	±
		4 PLC	±
		ANGLES	±
MATERIAL		FINISH	
-		-	
-		-	

NAME	HMM	
	MM PIN CONTACT	
	L=35	
SIZE	CAGE CODE	DRAWING NO
A2	00779	C-T2040051XXX001
CUSTOMER DRAWING		RESTRICTED TO
SCALE 4:1		SHEET 1 OF 1
		REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)