

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

LOC

DIST

REVISIONS

© COPYRIGHT 20 Tyco Electronics AMP GmbH ALL RIGHTS RESERVED.

AL

2

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D5	REVISED	21AUG2012	MZ	JC
	D6	REVISED PER ECR-13-009678	18SEP2013	RS	DD
	D7	ECR-16-004670	04APR2016	RS	JL

TYPICAL APPLICATION

Dimensions: 21.9, 9.9, 9.7, 3.7, 3.4, 1.8, 1740259-X, 293309-X, 293310-1

SECTION A-A
SCALE 4:1

PRINTED CIRCUIT BOARD LAYOUT FOR LOW VOLTAGE VERSION

TOLERANCES UNLESS OTHERWISE SPECIFIED ± 0.05
PRINTED CIRCUIT BOARD THICKNESS: 1.6 mm NOMINAL

Dimensions: 4.2 ± 0.1 , 7.4, 5.6, $\phi 1.1 \pm 0.1$ 2x, $\phi 1.5 \pm 0.1$ 2x UNPLATED

PRINTED CIRCUIT BOARD LAYOUT FOR HIGH VOLTAGE VERSION

TOLERANCES UNLESS OTHERWISE SPECIFIED ± 0.05
PRINTED CIRCUIT BOARD THICKNESS: 1.6 mm NOMINAL

Dimensions: 4.2, 1.0, 3, 1, 4, 7.4, 5.6, $\phi 1.1 \pm 0.1$ 2x, $\phi 1.5 \pm 0.1$ 2x UNPLATED, SLOT

HIGH VOLTAGE

KEYING HV-1

KEYING HV-2

KEYING HV-3

LOW VOLTAGE

KEYING LV-1

KEYING LV-2

1) MATERIALS:
CONTACTS: SOLDERING SIDE TIN PLATED Ph. BRONZE
RECEPTACLE IN SPECIAL ALLOY COPPER TIN PLATED
HOUSING: PA66 GFF25 UL 94 V0

2 OBSOLETE

2

2

LV-2	LOW-VOLT 42 V DC	293311-6	D	YELLOW
LV-1	LOW-VOLT 42 V AC	293311-5	D	LIGHT GREY
HV-2	SWITCH MAX. 7A	293311-4	D	RED
HV-3	HIGH-VOLT 125 V AC	293311-3	D	BLUE
HV-1	HIGH-VOLT 250 V AC	293311-2	D	BLACK
HV-1	HIGH-VOLT 250 V AC	293311-1	D	WHITE
KEYING	REMARKS	PART NUMBER	REV.	COLOR

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN R. FRABONI 18JUN2007

CHK -

APVD G. TURCO

PRODUCT SPEC 108-94018

APPLICATION SPEC 114-32102

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS:
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	\pm
1 PLC	± 0.5
2 PLC	± 0.3
3 PLC	\pm
4 PLC	\pm
ANGLES	$\pm 0.5^\circ$
FINISH	-

MATERIAL -

STE

TE Connectivity

NAME
7.5 mm PCB CONNECTOR ASSEMBLY
90 DEGREE FEMALE VERSION

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A300779 C-293311

SCALE 5:1 SHEET 1 OF 1 REV D7

1470-19 (3/11)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)