

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
H2		REVISED PER ECO-11-004587	11MAR11	RK	HMR
J		REVISED PER ECR-16-017870	20APR2017	BDA	MZ
K		REVISED PER ECO-18-000967	23MAR2018	RS	MZ

1.125±.025  
 .844±.010  
 1.25±.025  
 .844±.010  
 FLANGED

.809 MAX  
 .420±.015  
 .094±.010  
 5/8-24 UNEF-2A  
 Ø.688±.010  
 Ø.630 MAX  
 .125 MAX  
 PANEL THK

.844±.010  
 Ø.840  
 .844±.010  
 Ø.125 +.007  
 - .000  
 4 PLC

RECOMMENDED PANEL CUTOUT  
 SCALE 2:1

Ø.935 MAX  
 .817 MAX  
 FREE HANGING

A HOLE  
 4 PLC

STANDARD	YES	4-40 BRASS THREADED INSERT	20	FLANGED	△5 206433-6
SMALL PACK	NO	.125 DIA	20	FLANGED	206433-5
STANDARD	NO	.125 DIA	20DF WITHOUT INSULATION SUPPORT	FLANGED	△5 206433-4
STANDARD	NO	4-40 BRASS THREADED INSERT	20	FLANGED	206433-3
STANDARD	NO	-	20	FREE HANGING	206433-2
STANDARD	NO	.125 DIA	20	FLANGED	206433-1
PACKAGING	PERIPHERAL SEAL	A	WILL ACCEPT SOCKET CONTACT SIZE	TYPE	PART NUMBER

1 CONTACT CAVITIES IDENTIFIED BY CHARACTERS ON FRONT AND REAR FACE.  
 2 AMP MOLDED ON THIS SURFACE.  
 3 PART NUMBER AND DATE CODE MARKED ON ANY FLANGE EDGE.  
 4 206433-4 STRIPPED WIRE LENGTH SHOULD BE .193-.213 WITH .095 MAX INSULATION.  
 5 OBSOLETE PART NUMBER.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN J. McCLINTON 1-25-88	TE Connectivity Ltd.
	0 PLC ± -	CHK R. STONE 1-26-88	
	1 PLC ± -	APVD M. KAPEZYNSKI 1-27-88	
	2 PLC ± -	NAME	RECEPTACLE ASSEMBLY, ARRANGEMENT 11-8 REVERSE SEX, CPC
	3 PLC ± .005	PRODUCT SPEC	
	4 PLC ± -	APPLICATION SPEC	SIZE CAGE CODE DRAWING NO
	ANGLES ± -	FINISH	A2 00779 C-206433
MATERIAL NYLON, GLASS FILLED, FLAME RETARDED, BLACK	FINISH	WEIGHT	RESTRICTED TO
			CUSTOMER DRAWING
			SCALE 4:1 SHEET 1 OF 1 REV K

1471-9 (1/15)

Downloaded From [Onevac.com](http://Onevac.com)

206433

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)