

# SPECIFICATION CONTROL DRAWING

55PC6017

TITLE

THREE CONDUCTOR CABLE, FLAT BRAID SHIELDED, JACKETED, 600 VOLT

Date

1-25-93

Revision


A

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0214

SHIELD - SILVER-COATED COPPER

JACKET - RADIATION-CROSSLINKED, MODIFIED ETFE



## CONSTRUCTION DETAILS

PART NUMBER	CONDUCTOR SIZE (AWG)	SHIELD STRAND THICKNESS ( $\pm .0004$ )	JACKET THICKNESS (in.)		DIAMETER (in.)		WEIGHT (lbs/1000 ft.)		
			LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC6017-26*	26	.0015	.0060	.0080	.094	.089	104	7.91	8.50
55PC6017-24*	24	.0015	.0060	.0080	.105	.110	.115	10.21	10.85
55PC6017-22*	22	.0015	.0065	.0085	.119	.124	.129	13.70	14.44
55PC6017-20*	20	.0015	.0065	.0085	.137	.142	.147	19.04	19.92
55PC6017-18*	18	.0015	.0065	.0085	.157	.163	.169	26.67	27.77
55PC6017-16*	16	.0015	.0070	.0090	.174	.180	.186	33.02	34.26

## CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms)

DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz

CROSSLINKING PROOF TEST: 300  $\pm$  3°C for 1 hour

JACKET COLOR: White preferred

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 50% (minimum)

Tensile Strength, 5000 lb/ft<sup>2</sup> (minimum)

JACKET FLAWS:

Spark Test, 1000 volts (rms), 60 Hz, 100% test

Impulse Dielectric Test, 6.0 kV (peak), 100 % test

SHIELD COVERAGE: 85% (minimum)  
VOLTAGE WITHSTAND TEST (POST ENVIRONMENTAL):  
1000 volts (rms), 60 Hz, 1 minute

## PART NUMBER:

The \*\* in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.

Example: AWG 24, red, blue and yellow component wires;  
white jacket: 55PC6017-24-2/6/4-9

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-881

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)