



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 <sub>1</sub>	RELEASED	12/19/96	<i>PJA</i>

DESIGNED FOR USE WITH 0.085 SR CABLE	
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.089
CONTACT	.0204

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
EMI GASKET	CONDUCTIVE ELASTOMER PER MIL-G-83528	N/A

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY <i>JANDAR</i>	DATE 8/8/96	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599		
	CHECKED BY				
FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°	APPD BY <i>PJA</i>	12/19/96	<b>AMP</b> TITLE FIELD REPLACEABLE 2-HOLE FLANGE MOUNT JACK RECEPTACLE DIRECT SOLDER ATTACHMENT
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			USE ASSY PROCEDURE  408-04880 NO. A.P. (90-025)	SIZE B CODE IDENT NO. 26805 SCALE 5:1	

NOTES:  
1. CAPTURED CENTER CONTACT

.XXX = in  
XX.X = mm (REF)

CUSTOMER DRAWING

AMP PART # 1082124-1  
SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)