



- ⚠ HOUSING AND LATCHES: PCT, UL94 V-0 RATED, COLOR RED. POSTS: BRASS.
- ⚠ POSTS: GOLD FLASH OVER PALLADIUM-NICKEL PLATE, 0.76μm[.000030] MIN TOTAL ON THE LOCALIZED PLATE AREA, 2.54μm[.000100] MIN TIN PLATE ON THE SOLDER-TAIL, 1.27μm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST. -OR- 0.76μm[.000030] MIN GOLD PLATE ON THE LOCALIZED PLATE AREA, 2.54μm[.000100] MIN TIN PLATE ON THE SOLDER-TAIL, 1.27μm[.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
- ⚠ DISTANCE REQUIRED BY LATCHES IN OPEN POSITION.
- ⚠ RECOMMENDED PRINTED CIRCUIT BOARD THICKNESS 1.57 [.062].
- ⚠ RECOMMENDED PAD THICKNESS 0.25 [.010].
- ⚠ DATUMS -M- & -N- TO BE ESTABLISHED BY CUSTOMER.

	60.98 [2.400]	68.58 [2.700]	72.64 [2.860]	78.74 [3.100]	82.80 [3.260]	50	1-5111922-0
	30.48 [1.200]	38.10 [1.500]	42.16 [1.660]	48.26 [1.900]	53.32 [2.060]	26	5111922-6
OBSOLETE	48.26 [1.900]	55.88 [2.200]	59.94 [2.360]	66.04 [2.600]	70.10 [2.760]	40	5111922-9
OBSOLETE	17.78 [.700]	25.40 [1.000]	29.46 [1.160]	35.56 [1.400]	39.62 [1.560]	16	5111922-3
OBSOLETE	10.16 [.400]	17.78 [.700]	21.84 [.860]	27.94 [1.100]	32.00 [1.260]	10	5111922-1
	E	D	C	B	A	NUMBER OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009.

STE TE Connectivity

APPROVED: M. WALMSLEY, NAME: M. WALMSLEY, DATE: 01-12-05

PRODUCT SPEC: 108-40018

APPLICATION SPEC: -

SIZE: A1, CASE CODE: 00779, DRAWING NO: 5111922, RESTRICTED TO: -

CUSTOMER DRAWING, SCALE: 4:1, SHEET: 1 OF 1, REV: E

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)